



### Fittings with swivel flange

#### • HG-45FL 45° Elbow Swivel Flange, IP66

45° elbow swivel flange.

#### Features and Benefits

- One piece, fast fit
- High pull-off strength
- Highly resistant to solvents and oils
- Free of halogen, sulphur and phosphorus

Technical Table

Article-No.	Type	Nominal Ø	Pack Cont.
166-23600	<b>HG16-45FL</b>	16	10
166-23601	<b>HG21-45FL</b>	21	10
166-23602	<b>HG28-45FL</b>	28	10
166-23603	<b>HG34-45FL</b>	34	10
166-23604	<b>HG42-45FL</b>	42	2

All dimensions in mm. Subject to technical changes.

Colour grey available on request.



HelaGuard HG-45FL 45° Elbow Swivel Flange, IP66.

Material Data

Material	<b>Polyamide 6.6 (PA66)</b>
Colour	<b>Black (BK)</b>
Operating Temperature	<b>-50 °C to +135 °C</b>
Flammability	<b>UL94 V2</b>



#### • HGL-45FL 45° Elbow Swivel Flange, IP68

45° elbow swivel flange with conduit seal and washer.

Fulfils IP66, IP67, IP68 and IP69k.

#### Features and Benefits

- One piece, fast fit
- High pull-off strength
- Highly resistant to solvents and oils
- Free of halogen, sulphur and phosphorus

Technical Table

Article-No.	Type	Nominal Ø	Pack Cont.
166-24200	<b>HGL16-45FL</b>	16	10
166-24201	<b>HGL21-45FL</b>	21	10
166-24202	<b>HGL28-45FL</b>	28	10
166-24203	<b>HGL34-45FL</b>	34	10
166-24204	<b>HGL42-45FL</b>	42	2

All dimensions in mm. Subject to technical changes.

Colour grey available on request.



HelaGuard HGL-45FL 45° Elbow Swivel Flange, IP68.



Please note! Not all products listed on this page may have this approval.  
For product specific approvals please refer to the Appendix.