



### Connectors, reducers and couplers

#### • HG-Y Y-Connector, IP66

##### Features and Benefits

- Fast fit Y-connector
- Branches reduce conduit size
- High pull-off strength
- Highly resistant to solvents and oils
- Free of halogen, sulphur and phosphorus



HelaGuard HG-Y, Y-Connector, IP66.

Technical Table

Article-No.	Type	Entry nominal diameter	Exit nominal diameter	Pack Cont.
166-25801	<b>HG16-Y13</b>	16	13	5
166-25802	<b>HG21-Y16</b>	21	16	3
166-25803	<b>HG28-Y21</b>	28	21	3
166-25804	<b>HG34-Y28</b>	34	28	2

All dimensions in mm. Subject to technical changes.

Colour grey available on request.

Material Data

Material	<b>Polyamide 6.6 (PA66)</b>
Colour	<b>Black (BK)</b>
Operating Temperature	<b>-50 °C to +135 °C</b>
Flammability	<b>UL94 V2</b>



#### • HGL-Y Y-Connector, IP68

Fulfills IP66, IP67, IP68 and IP69k.

##### Features and Benefits

- Fast fit Y-connector
- Branches reduce conduit size
- High pull-off strength
- Highly resistant to solvents and oils
- Free of halogen, sulphur and phosphorus



HelaGuard HGL-Y, Y-Connector with conduit seals.

Technical Table

Article-No.	Type	Entry nominal diameter	Exit nominal diameter	Pack Cont.
166-25901	<b>HGL16-Y13</b>	16	13	5
166-25902	<b>HGL21-Y16</b>	21	16	3
166-25903	<b>HGL28-Y21</b>	28	21	3
166-25904	<b>HGL34-Y28</b>	34	28	2

All dimensions in mm. Subject to technical changes.

Colour grey available on request.



Please note! Not all products listed on this page may have this approval.  
For product specific approvals please refer to the Appendix.