



Asset tracking labels, thermal transfer

- **Material 1205 (White), removable**

Features and Benefits

Barcoding, complex data sets and tracking numbers can be printed on these temporary tracking labels. The specially engineered adhesive compound is designed to leave no sticky residue so making it ideal for use during the production of pc's, laptops, and monitors.

A secondary application can be where products need to be painted or sprayed over without damaging or defacing the original product label. The weak bonding characteristics of this material ensures that both the label and its text remain in place.

For problem-free printing, we recommend Tagprint Pro software.



Easy to apply and simple to remove.



Thermal Transfer Printer



Material Data	
Material	Type 1205, Polyester (PET), white (WH), removable
Operating Temperature	-40 °C to +120 °C
Curing Temperature	from 0 °C
Recommended Ribbon Type	TT822OUT
Adhesive	Acrylic
Thickness of Foil (µm)	58
Chem. Material Properties	Excellent resistance to water, alcohol, most oils, greases, fuel, aliphatic solvents, weak acids, salts and alkalis.



Technical Table

Article-No.	Type	Colour	Width (W)	Height (H)	Width of Liner (WL)	Labels per Row	Pack Cont.
596-12013	TAG13TD4-1205	White (WH)	19.05	6.35	101.60	4	10000
596-12015	TAG15TD3-1205	White (WH)	25.40	12.70	85.09	3	7500
596-12031	TAG31TD3-1205	White (WH)	25.40	19.05	85.09	3	5000
596-12027	TAG27TD2-1205	White (WH)	38.10	19.05	85.09	2	2500
596-12577	TAG77TD1-1205	White (WH)	50.80	22.86	55.00	1	2000
596-12473	TAG73TD1-1205	White (WH)	50.80	25.40	55.00	1	2000
596-12576	TAG76TD1-1205	White (WH)	63.50	50.80	70.00	1	500

All dimensions in mm. Subject to technical changes.

