



Cable Ties in-between size to T-Series


• LK-Series

Features and Benefits

Available in a wide range of materials, these cable ties all feature internal serrations allowing for a positive hold onto cable, hose and pipe bundles. The design of the head guarantees a high tensile strength whilst allowing a very low insertion force, this, combined with the bent tail design of many of the ties ensures a simple and quick installation. Whilst easily installed by hand manual, and pneumatic (for high volume applications) tensioning tools are available to ensure a consistent and safe installation.

Application

For routing, bundling and securing of cables, pipes and hoses.



LK Series Industrial Ties

Material Data		
Material	Polyamide 6.6 UV Resistant (PA66W)	
Operating Temperature	-40 °C to +85 °C Continuous, (+105 °C for 500 h)	
Flammability	UL94 V2	



Material Data		
Material	Polyamide 6.6 Heat Stabilised (PA66HS)	
Operating Temperature	-40 °C to +105 °C Continuous, (+145 °C for 500 h)	
Flammability	UL94 V2	



Material Data		
Material	Polyamide 6.6 High Imp. Mod. scan black (PA66HIR(S))	
Operating Temperature	-40 °C to +80 °C Continuous, (+105 °C for 500 h)	
Flammability	UL94 HB	



Material Data		
Material	Polyamide 6.6 (PA66)	
Operating Temperature	-40 °C to +85 °C Continuous, (+105 °C for 500 h)	
Flammability	UL94 V2	



Technical Table

Article-No.	Type	Length (L)	Width (W)	Bundle Ø max.	Min. Tensile Strength (N)	Material	Colour	Application Tool
LK2								
111-60219	LK2	120	4.8	28.0	135	PA66	Natural (NA)	1-10
111-60210	LK2	120	4.8	28.0	135	PA66	Black (BK)	1-10
LK2A								
111-60119	LK2A	270	4.6	73.0	225	PA66	Natural (NA)	1-10
111-60110	LK2A	270.0	4.6	73.0	225	PA66	Black (BK)	1-10
111-60160	LK2A	270	4.6	73.0	225	PA66W	Black (BK)	1-10
111-60159	LK2A	270	4.6	73.0	225	PA66HS	Natural (NA)	1-10
111-60150	LK2A	270.0	4.6	73.0	225	PA66HS	Black (BK)	1-10
111-00127	LK2A	270	4.6	73.0	225	PA66HIR(S)	Black (BK)	1-10
LK5								
111-60519	LK5	535	13.2	150	1115	PA66	Natural (NA)	8, 9
111-60510	LK5	535	13.2	150	1115	PA66	Black (BK)	8, 9
111-60560	LK5	535	13.2	150	1115	PA66W	Black (BK)	8, 9
111-60559	LK5	535	13.2	150	1115	PA66HS	Natural (NA)	8, 9
111-60501	LK5	535	13.2	150	1115	PA66HIR(S)	Black (BK)	8, 9

All dimensions in mm. Subject to technical changes.



Please note! Not all products listed on this page may have this approval.

For product specific approvals please refer to the Appendix.