



Fittings for metallic conduits with plastic coating and metallic overbraid

• PCSB-SMC Swivel Thread Compression Fitting, IP65

Swivel external thread, nickel plated brass.
Fulfils IP65.

Features and Benefits

- Multipart compression fitting including elastomeric seal
- Can be used for knockouts or threaded entries as fitting rotates until tightened
- Braid is locked between inner and outer compression nuts



HelaGuard PCSB-SMC Swivel Compression Fitting.

Technical Table

Article-No.	Type	Nominal Ø	Thread Size (metric)	Pack Cont.
166-34200	PCSB16-SMC-M16	16	M16	10
166-34201	PCSB16-SMC-M20	16	M20	10
166-34202	PCSB20-SMC-M20	20	M20	10
166-34203	PCSB25-SMC-M25	25	M25	10
166-34204	PCSB32-SMC-M32	32	M32	2

All dimensions in mm. Subject to technical changes.

Material Data

Material	Nickel Plated Brass (NPB), Polyamide 6 (PA6)
Colour	Metal (ML)
Operating Temperature	-40 °C to +135 °C



• PCSB-90FMC 90° Elbow Compression Fitting, IP65

External thread elbow, nickel plated brass.
Fulfils IP65.

Features and Benefits

- Multipart 90° compression fitting including elastomeric seal
- Braid is locked between inner and outer compression nuts



HelaGuard PCSB-90FMC Swivel Compression Fitting.

Technical Table

Article-No.	Type	Nominal Ø	Thread Size (metric)	Pack Cont.
166-34300	PCSB16-90FMC-M16	16	M16	10
166-34301	PCSB16-90FMC-M20	16	M20	10
166-34302	PCSB20-90FMC-M20	20	M20	10
166-34303	PCSB25-90FMC-M25	25	M25	10
166-34304	PCSB32-90FMC-M32	32	M32	2

All dimensions in mm. Subject to technical changes.