



HelaGuard Metallic Conduits with Liquid-Tight Cover and Fittings

Fittings for metallic conduits with liquid-tight cover

• LTS-LTS Compression Coupler, IP68

Nickel plated brass.
Fulfils IP66, IP67 and IP68.

Features and Benefits

- Multipart compression coupler including polyamide seals
- Joins two conduits



HelaGuard LTS-LTS Compression Coupler.

Technical Table

Article-No.	Type	Nominal Ø	Pack Cont.
166-32600	LTS20-LTS20	20	10
166-32601	LTS25-LTS25	25	10

All dimensions in mm. Subject to technical changes.

Material Data

Material	Nickel Plated Brass (NPB), Polyamide 6 (PA6)
Colour	Metal (ML)
Operating Temperature	-40 °C to +135 °C



• LTS-SCG Straight cable gland fitting, IP68

External thread, nickel plated brass.
Fulfils IP66, IP67, IP68 and IP69k.

Features and Benefits

- Multipart compression fitting including elastomeric seal
- Strain relief
- Cable seal at IP68 and IP69k



LTS-SCG Compression Fitting with Strain Relief and Cable Seal.

Technical Table

Article-No.	Type	Nominal Ø	Thread Size (metric)	Suitable for Cable Ø from/to	Pack Cont.
166-36201	LTS16-SCG-M16	16	M16	4.5 - 10	10
166-36202	LTS20-SCG-M20	20	M20	7 - 13	10
166-36203	LTS25-SCG-M25	25	M25	9 - 17	10
166-36204	LTS32-SCG-M32	32	M32	11 - 21	2

All dimensions in mm. Subject to technical changes.

Material Data

Material	Polyamide 6.6 (PA66), Nickel Plated Brass (NPB), Thermoplastic Elastomer (TPE)
Colour	Metal (ML)
Operating Temperature	-40 °C to +135 °C

