



## Aluminum electrolytic capacitors

### Single-ended capacitors

Series/Type: B41002

Date: December 2010


## General-purpose grade capacitors

## Applications

- Low profile applications

## Features

- RoHS-compatible
- Ultra compact height up to 7 mm
- Suitable to replace low cost tantalum capacitors
- Useful life of 1000 h at 85 °C



## Construction

- Radial leads
- Aluminum case with insulating sleeve
- Charge-discharge proof
- Minus pole marking on the insulating sleeve
- Case with safety vent from diameter 8 mm


## Delivery mode

- Bulk
- Taped, Ammo pack
- Cut (see chapter "Single-ended Taping, packing and lead configurations, Cut leads (Chapter A)")
- Kinked (see chapter "Single-ended Taping, packing and lead configurations, Kinked leads (Chapter A)")

Refer to chapter "Single-ended capacitors Taping, packing and lead configurations" for further details.


**Specifications and characteristics in brief**

Rated voltage $V_R$	6.3 ... 63 V DC						
Surge voltage $V_S$	$1.15 \cdot V_R$ (at room temperature)						
Rated capacitance $C_R$	0.1 ... 330 $\mu\text{F}$						
Capacitance tolerance	$\pm 20\%$ M						
Dissipation factor $\tan d$ (20 °C, 120 Hz)	For capacitance higher than 1000 nF add 0.02 for every increase of 1000 nF.						
	$V_R$ (V DC)	6.3	10	16	25	35	50
	$\tan d$	0.24	0.20	0.16	0.14	0.12	0.10
							0.08
Leakage current $I_{\text{leak}}$ (20 °C, after 5 minutes)	$I_{\text{leak}} \leq 0.01 \mu\text{A} \cdot \left( \frac{C_R}{\mu\text{F}} \cdot \frac{V_R}{V} \right)$ or 3 $\mu\text{A}$ , whichever is greater						
Useful life $85^\circ\text{C}; V_R; I_{\text{AC},R}$	$> 1000$ h						
Requirements	DC/C $\pm 20\%$ of initial value tan d $\pm 2$ times initial specified value $I_{\text{leak}}$ initial specified limit						
Shelf life	After storage for 500 h at 85 °C, the capacitors shall meet the requirement of load life test after reforming process. After test: $V_R$ to be applied for 30 minutes, 24 to 48 hours before measurement.						
Low temperature stability (impedance ratio) (120 Hz)	$V_R$ (V DC)	6.3	10 ... 16	25 ... 63			
	$Z (-40^\circ\text{C})$	7	5	4			
	$Z (+20^\circ\text{C})$						
Vibration resistance test	To IEC 60068-2-6, test Fc: Frequency range 10 ... 55 Hz, displacement amplitude 0.75 mm, acceleration max. 10 g, duration 3 ' 2 h. Capacitor is mounted by the leads.						
IEC climatic category	To IEC 60068-1: 40/085/56 (-40 °C/+85 °C/56 days damp heat test)						


**B41002**
**Compact 85 °C**
**Dimensional drawing**

**Safety vent for diameter<sup>3</sup> 8 mm.**
**Case Dimensions**

$d \text{ ' } l$ mm	$d_{\max} \text{ ' } l_{\max}$ mm	a mm	b mm
4 ' 7	4.5 ' 8.0	$1.5 \pm 0.5$	$0.45 \pm 0.05$
5 ' 7	5.5 ' 8.0	$2.0 \pm 0.5$	$0.45 \pm 0.05$
6.3 ' 7	6.8 ' 8.0	$2.5 \pm 0.5$	$0.45 \pm 0.05$
8 ' 7	8.5 ' 8.5	$3.5 \pm 0.5$	$0.50 \pm 0.05$


**Overview of available types**

$V_R$ (V DC)	6.3	10	16	25	35	50	63
Case dimensions d ' l (mm)							
$C_R$ (mF)							
0.10						4 ' 7	4 ' 7
0.15						4 ' 7	4 ' 7
0.22						4 ' 7	4 ' 7
0.33						4 ' 7	4 ' 7
0.47						4 ' 7	4 ' 7
0.68						4 ' 7	4 ' 7
1.0					4 ' 7	4 ' 7	4 ' 7
1.5					4 ' 7	4 ' 7	4 ' 7
2.2					4 ' 7	4 ' 7	4 ' 7
3.3				4 ' 7	4 ' 7	4 ' 7	5 ' 7
4.7			4 ' 7	4 ' 7	4 ' 7	4 ' 7	5 ' 7
6.8			4 ' 7	4 ' 7	4 ' 7	5 ' 7	6.3 ' 7
10			4 ' 7	4 ' 7	5 ' 7	5 ' 7	6.3 ' 7
15		4 ' 7	4 ' 7	5 ' 7	5 ' 7	6.3 ' 7	
22	4 ' 7	4 ' 7	4 ' 7	5 ' 7	6.3 ' 7	8 ' 7	
33	4 ' 7	4 ' 7	5 ' 7	6.3 ' 7	6.3 ' 7	8 ' 7	
47	5 ' 7	5 ' 7	6.3 ' 7	6.3 ' 7	8 ' 7		
68	5 ' 7	6.3 ' 7	6.3 ' 7	8 ' 7			
100	6.3 ' 7	6.3 ' 7	8 ' 7	8 ' 7			
220	8 ' 7	8 ' 7	8 ' 7				
330	8 ' 7						


**B41002**

Compact 85 °C

## Technical data and ordering codes

$C_R$ 120 Hz, 20 °C nF	Case dimensions d ' l mm	$I_{AC,R}$ 120 Hz, 85 °C mA	Ordering code (composition see below)
<b><math>V_R = 6.3</math> V DC</b>			
22	4 ' 7	35	B41002A2226M***
33	4 ' 7	40	B41002A2336M***
47	5 ' 7	50	B41002A2476M***
68	5 ' 7	60	B41002A2686M***
100	6.3 ' 7	80	B41002A2107M***
220	8 ' 7	130	B41002A2227M***
330	8 ' 7	190	B41002A2337M***
<b><math>V_R = 10</math> V DC</b>			
15	4 ' 7	28	B41002A3156M***
22	4 ' 7	35	B41002A3226M***
33	4 ' 7	45	B41002A3336M***
47	5 ' 7	60	B41002A3476M***
68	6.3 ' 7	75	B41002A3686M***
100	6.3 ' 7	90	B41002A3107M***
220	8 ' 7	160	B41002A3227M***
<b><math>V_R = 16</math> V DC</b>			
4.7	4 ' 7	20	B41002A4475M***
6.8	4 ' 7	25	B41002A4685M***
10	4 ' 7	30	B41002A4106M***
15	4 ' 7	35	B41002A4156M***
22	4 ' 7	40	B41002A4226M***
33	5 ' 7	55	B41002A4336M***
47	6.3 ' 7	68	B41002A4476M***
68	6.3 ' 7	80	B41002A4686M***
100	8 ' 7	100	B41002A4107M***
220	8 ' 7	160	B41002A4227M***

## Composition of ordering code

\*\*\* = Version

000 = for standard leads, bulk

001 = for kinked leads, bulk

002 = for cut leads, bulk

 016 = for taped leads, Ammo pack, lead spacing F = 2.0 mm (for  $\Delta E$  4 ... 5 mm)

 007 = for taped leads, Ammo pack, lead spacing F = 2.5 mm (for  $\Delta E$  4 ... 6.3 mm)

 006 = for taped leads, Ammo pack, lead spacing F = 3.5 mm (for  $\Delta E$  8 mm)

 008 = for taped leads, Ammo pack, lead spacing F = 5.0 mm (for  $\Delta E$  5 ... 8 mm)



## Technical data and ordering codes

$C_R$ 120 Hz, 20 °C nF	Case dimensions d ' l mm	$I_{AC,R}$ 120 Hz, 85 °C mA	Ordering code (composition see below)
<b><math>V_R = 25</math> V DC</b>			
3.3	4 ' 7	15	B41002A5335M***
4.7	4 ' 7	20	B41002A5475M***
6.8	4 ' 7	25	B41002A5685M***
10	4 ' 7	29	B41002A5106M***
15	5 ' 7	35	B41002A5156M***
22	5 ' 7	49	B41002A5226M***
33	6.3 ' 7	60	B41002A5336M***
47	6.3 ' 7	80	B41002A5476M***
68	8 ' 7	100	B41002A5686M***
100	8 ' 7	125	B41002A5107M***
<b><math>V_R = 35</math> V DC</b>			
1.0	4 ' 7	8.0	B41002A7105M***
1.5	4 ' 7	10	B41002A7155M***
2.2	4 ' 7	13	B41002A7225M***
3.3	4 ' 7	16	B41002A7335M***
4.7	4 ' 7	22	B41002A7475M***
6.8	4 ' 7	26	B41002A7685M***
10	5 ' 7	31	B41002A7106M***
15	5 ' 7	40	B41002A7156M***
22	6.3 ' 7	52	B41002A7226M***
33	6.3 ' 7	70	B41002A7336M***
47	8 ' 7	95	B41002A7476M***
<b><math>V_R = 50</math> V DC</b>			
0.1	4 ' 7	1.0	B41002A6104M***
0.15	4 ' 7	1.5	B41002A6154M***
0.22	4 ' 7	2.3	B41002A6224M***
0.33	4 ' 7	3.5	B41002A6334M***
0.47	4 ' 7	5.0	B41002A6474M***
0.68	4 ' 7	8.0	B41002A6684M***

## Composition of ordering code

\*\*\* = Version

000 = for standard leads, bulk

001 = for kinked leads, bulk

002 = for cut leads, bulk

016 = for taped leads, Ammo pack, lead spacing F = 2.0 mm (for  $\Delta$ 4 ... 5 mm)007 = for taped leads, Ammo pack, lead spacing F = 2.5 mm (for  $\Delta$ 4 ... 6.3 mm)006 = for taped leads, Ammo pack, lead spacing F = 3.5 mm (for  $\Delta$ 8 mm)008 = for taped leads, Ammo pack, lead spacing F = 5.0 mm (for  $\Delta$ 5 ... 8 mm)


**B41002**

Compact 85 °C

## Technical data and ordering codes

$C_R$ 120 Hz, 20 °C nF	Case dimensions d ' l mm	$I_{AC,R}$ 120 Hz, 85 °C mA	Ordering code (composition see below)
<b><math>V_R = 50</math> V DC</b>			
1.0	4 ' 7	10	B41002A6105M***
1.5	4 ' 7	13	B41002A6155M***
2.2	4 ' 7	16	B41002A6225M***
3.3	4 ' 7	22	B41002A6335M***
4.7	4 ' 7	26	B41002A6475M***
6.8	5 ' 7	30	B41002A6685M***
10	5 ' 7	38	B41002A6106M***
15	6.3 ' 7	44	B41002A6156M***
22	8 ' 7	60	B41002A6226M***
33	8 ' 7	90	B41002A6336M***
<b><math>V_R = 63</math> V DC</b>			
0.1	4 ' 7	1.0	B41002A8104M***
0.15	4 ' 7	1.5	B41002A8154M***
0.22	4 ' 7	2.3	B41002A8224M***
0.33	4 ' 7	3.5	B41002A8334M***
0.47	4 ' 7	5.0	B41002A8474M***
0.68	4 ' 7	8.0	B41002A8684M***
1.0	4 ' 7	10	B41002A8105M***
1.5	4 ' 7	13	B41002A8155M***
2.2	4 ' 7	16	B41002A8225M***
3.3	5 ' 7	23	B41002A8335M***
4.7	5 ' 7	30	B41002A8475M***
6.8	6.3 ' 7	35	B41002A8685M***
10	6.3 ' 7	40	B41002A8106M***

## Composition of ordering code

\*\*\* = Version

000 = for standard leads, bulk

001 = for kinked leads, bulk

002 = for cut leads, bulk

 016 = for taped leads, Ammo pack, lead spacing F = 2.0 mm (for  $\varnothing$ 4 ... 5 mm)

 007 = for taped leads, Ammo pack, lead spacing F = 2.5 mm (for  $\varnothing$ 4 ... 6.3 mm)


 006 = for taped leads, Ammo pack, lead spacing F = 3.5 mm (for  $\varnothing$ 8 mm)

 008 = for taped leads, Ammo pack, lead spacing F = 5.0 mm (for  $\varnothing$ 5 ... 8 mm)




### Useful life

depending on ambient temperature  $T_A$  under ripple current operating conditions<sup>1)</sup>



Frequency factor of permissible ripple current  $I_{AC}$  versus frequency  $f$



1) Refer to chapter "General technical information, 5.3 Calculation of useful life" for an explanation on how to interpret the useful life graphs.


**B41002**
**Compact 85 °C**

## Taping, packing and lead configurations

### Taping

Single-ended capacitors are available taped in Ammo pack from diameter 4 to 18 mm as follows:

Lead spacing F = 2.0 mm ( $\Delta E d = 4 \dots 5$  mm)

Lead spacing F = 2.5 mm ( $\Delta E d = 4 \dots 6.3$  mm)


Lead spacing F = 3.5 mm ( $\Delta E d = 8$  mm)

Lead spacing F = 5.0 mm ( $\Delta E d = 4 \dots 12.5$  mm)

Lead spacing F = 7.5 mm ( $\Delta E d = 16 \dots 18$  mm).

Lead spacing 2.0 mm ( $\Delta E d = 4 \dots 5$  mm)

Last 3 digits of ordering code: 016




### Dimensions in mm

$\Delta E d$	F	H	W	$W_0$	$W_1$	$W_2$	P	$P_0$	$P_1$	$I_1$	t	Dh	$D_0$
4 ... 5	2.0	18.5	18.0	7.0	9.0	3.0	12.7	12.7	5.10	1.0	0.7	1	4.0
	+0.8 -0.2	$\pm 0.75$	$\pm 0.5$	min.	$\pm 0.5$	max.	$\pm 1.0$	$\pm 0.3$	$\pm 0.7$	max.	$\pm 0.2$	$\pm 1.0$	$\pm 0.2$



Lead spacing 2.5 mm (  $\Delta d = 4 \dots 6.3$  mm)

Last 3 digits of ordering code: 007




Dimensions in mm

$\Delta d$	F	H	W	$W_0$	$W_1$	$W_2$	$H_0$	P	$P_0$	$P_1$	$I_1$	t	$Dh$	$D_0$
4 ... 6.3	2.5	18.5	18.0	5.5	9.0	1.5	16.0	12.7	12.7	5.1	1.0	0.7	1.0	4.0
Toler- ance	+0.8 0.2	±0.75 ±0.2	±0.5 min.	±0.5 max.	±0.5 max.	±0.5 ±1.0	±0.5 ±1.0	±0.2 ±0.2	±0.5 ±0.5	max.	±0.2 max.	±0.2 max.	±0.2 max.	±0.2 max.

Lead spacing 3.5 mm (  $\Delta d = 8$  mm)

Last 3 digits of ordering code: 006



Dimensions in mm

$\Delta d$	F	H	W	$W_0$	$W_1$	$W_2$	P	$P_0$	$P_1$	$I_1$	t	$Dh$	$D_0$
8	3.5	18.5	18.0	10	9.0	3.0	12.7	12.7	4.6	1.0	0.7	1.0	4.0
Toler- ance	+0.8 0.2	±1.0 ±0.5	±0.5 min.	±0.5 max.	±0.5 max.	±1.0 ±1.0	±0.3 ±0.3	±0.6 ±0.6	max.	±0.2 max.	max.	±0.2 max.	±0.2 max.


Leads can also run straight through the taping area. Taping is available up to dimensions  $d \cdot l = 8 \cdot 15$  mm.


**B41002**


Compact 85 °C

 Lead spacing 5.0 mm (  $\Delta\text{Ed} = 4 \dots 8 \text{ mm}$  )

Last 3 digits of ordering code: 008


 Lead spacing 5.0 mm (  $\Delta\text{Ed} = 10 \dots 12.5 \text{ mm}$  )

Last 3 digits of ordering code: 008




Dimensions in mm

$\Delta\text{Ed}$	F	H	W	$W_0$	$W_1$	$W_2$	$H_0$	P	$P_0$	$P_1$	$l_1$	t	$Dh$	$D_0$
4 ... 6.3	5.0	18.5	18.0	5.5	9.0	1.5	16.0	12.7	12.7	3.85	1.0	0.6	1.0	4.0
8		20.0		10.0			16.0	12.7	12.7	3.85				
10	5.0	19.0	18.0	12.5	9.0	1.5		12.7	12.7	3.85	1.0	0.6	1.0	4.0
12.5		19.0		12.5				15.0	15.0	5.0				
Tolerance	+0.8 0.2	$\pm 0.75$	$\pm 0.5$	min.	$\pm 0.5$	max.	$\pm 0.5$	$\pm 1.0$	$\pm 0.2$	$\pm 0.5$	max.	+0.3 0.2	max.	$\pm 0.2$


 Taping is available up to dimensions  $d' l = 12.5 \text{ } 25 \text{ mm}$ .

 Taping is not available for  $d' l = 8 \text{ } 20 \text{ mm}$ .



Lead spacing 7.5 mm ( $\Delta d = 16 \dots 18$  mm)

Last 3 digits of ordering code: 009



Dimensions in mm

$\Delta d$	F	H	W	$W_0$	$W_1$	$W_2$	P	$P_0$	$P_1$	$l_1$	t	DP	Dh	$D_0$
16	7.5	18.5	18.0	12.5	9.0	1.5	30.0	15.0	3.75	1.0	0.7	0	0	4.0
18														
Toler- ance	$\pm 0.8$	0.5	$\pm 0.5$	min.	$\pm 0.5$	max.	$\pm 1.0$	$\pm 0.2$	$\pm 0.5$	max.	$\pm 0.2$	$\pm 1.0$	$\pm 1.0$	$\pm 0.2$

Taping is available up to dimensions  $d \leq l = 16 \leq 31.5$  mm and  $18 \leq 31.5$  mm.


**B41002**
**Compact 85 °C**


### Cut or kinked leads

Single-ended capacitors are available with cut or kinked leads. Other lead configurations also available upon request.

### Cut leads (Chapter A)

Available for series B41002, B41022, B41044, B41827, B41828, B43044, B43082, B43086, B43088, B43827, B43828.

Last 3 digits of ordering code: 002



KAL1086-R

Case size d x l (mm)	Dimensions (mm) a ±0.5
4 x 7	1.5
5 x 7	2.0
5 x 11	2.0
6.3 x 7	2.5
6.3 x 11	2.5
8 x 7	3.5
8 x 11.5	3.5
8 x 15	3.5
8 x 20	3.5
10 x 12.5	5.0
10 x 16	5.0
10 x 20	5.0
10 x 25	5.0


Case size d x l (mm)	Dimensions (mm) a ±0.5
12.5 x 16	5.0
12.5 x 20	5.0
12.5 x 25	5.0
12.5 x 31.5	5.0
12.5 x 35.5	5.0
12.5 x 40	5.0
16 x 20	7.5
16 x 25	7.5
16 x 31.5	7.5
16 x 35.5	7.5
16 x 40	7.5
18 x 20	7.5
18 x 25	7.5
18 x 31.5	7.5
18 x 35.5	7.5
18 x 40	7.5


**Cut leads (Chapter B)**


Available for series B41858, B41859, B41863, B41866, B41868, B41888, B41890, B41896, B42824, B42851, B43866, B43867, B43890, B43896.

Last 3 digits of ordering code: 002

With stand-off rubber seal



With flat rubber seal





Case size $d \cdot l$ (mm)	Dimensions (mm) $a \pm 0.5$
10 ' 12.5	5.0
10 ' 16	5.0
10 ' 20	5.0
12.5 ' 20	5.0
12.5 ' 25	5.0
16 ' 20	7.5
16 ' 25	7.5
16 ' 31.5	7.5
16 ' 35.5	7.5
18 ' 20	7.5
18 ' 25	7.5
18 ' 31.5	7.5
18 ' 35	7.5
18 ' 40	7.5


**B41002**
**Compact 85 °C**
**Kinked leads (Chapter A)**

Available for series B41002, B41022, B41044, B41827, B41828, B43044, B43082, B43086, B43088, B43827, B43828.

Last 3 digits of ordering code: 001


**KAL1137-5**

**KAL1084-A**

Case size d x l (mm)	Dimensions (mm) a ± 0.5
4 x 7	1.5
5 x 7	2.0
5 x 11	2.0
6.3 x 7	2.5
6.3 x 11	2.5
8 x 7	3.5
8 x 11.5	3.5
8 x 15	3.5
8 x 20	3.5
10 x 12.5	5.0
10 x 16	5.0
10 x 20	5.0
10 x 25	5.0



Case size d x l (mm)	Dimensions (mm) a ± 0.5
12.5 x 16	5.0
12.5 x 20	5.0
12.5 x 25	5.0
12.5 x 31.5	5.0
12.5 x 35.5	5.0
12.5 x 40	5.0
16 x 20	7.5
16 x 25	7.5
16 x 31.5	7.5
16 x 35.5	7.5
16 x 40	7.5
18 x 20	7.5
18 x 25	7.5
18 x 31.5	7.5
18 x 35.5	7.5
18 x 40	7.5


**Kinked leads (Chapter B)**



Available for series B41858, B41859, B41863, B41866, B41868, B41888, B41890, B41896, B42824, B42851, B43866, B43867, B43890, B43896.

Last 3 digits of ordering code: 001

With stand-off rubber seal



With flat rubber seal



Case size $d \cdot l$ (mm)	Dimensions (mm) $a \pm 0.5$
10 ' 20	5.0
12.5 ' 20	5.0
12.5 ' 25	5.0
16 ' 20	7.5
16 ' 25	7.5
16 ' 31.5	7.5
16 ' 35.5	7.5
18 ' 20	7.5
18 ' 25	7.5
18 ' 31.5	7.5
18 ' 35	7.5
18 ' 40	7.5


**B41002**
**Compact 85 °C**

### PAPR leads (Protection Against Polarity Reversal)

These lead configurations ensure correct placement of the capacitor on the PCB with regard to polarity. PAPR leads are available for diameters from 10 mm up to 18 mm.


There are three configurations available: Crimped leads, J leads, bent 90° leads

Available for series B41858, B41859, B41863, B41866, B41868, B41888, B41890, B41896, B42824, B42851, B43866, B43867, B43890, B43896.


#### Crimped leads

Last 3 digits of ordering code: 003




#### With stand-off rubber seal



#### With flat rubber seal





#### Suggestion for PCB hole diameter



Case size d ' l (mm)	Dimensions (mm)					
	B ±0.2	C ±0.5	D ±0.1	E ±0.1	a ±0.5	A <b>ob</b>
16 ' 20	1.5	3.0	1.3	0.3	7.5	0.8 ±0.05
16 ' 25	1.5	3.0	1.3	0.3	7.5	0.8 ±0.05
16 ' 31.5	1.5	3.0	1.3	0.3	7.5	0.8 ±0.05
16 ' 35.5	1.5	3.0	1.3	0.3	7.5	0.8 ±0.05
18 ' 20	1.5	3.0	1.3	0.3	7.5	0.8 ±0.1
18 ' 25	1.5	3.0	1.3	0.3	7.5	0.8 ±0.1
18 ' 31.5	1.5	3.0	1.3	0.3	7.5	0.8 ±0.1
18 ' 35	1.5	3.0	1.3	0.3	7.5	0.8 ±0.1
18 ' 40	1.5	3.0	1.3	0.3	7.5	0.8 ±0.1



**J leads**

Last 3 digits of ordering code: 004




KAL1091-S-E

**Suggestion for PCB hole diameter**

Suggestion for PCB hole diameter,  
wire  $\phi 0.6$  mm


KAL1092-1-E

Suggestion for PCB hole diameter,  
wire  $\phi 0.8$  mm


KAL1093-9-E


Case size d ' l (mm)	Dimensions (mm)				
	C $\pm 0.5$	E $\pm 0.5$	J $\pm 0.2$	a $\pm 0.5$	A <sub>B</sub>
10 ' 12.5	3.2	0.7	1.2	5.0	0.6 $\pm 0.05$
10 ' 16	3.2	0.7	1.2	5.0	0.6 $\pm 0.05$
10 ' 20	3.2	0.7	1.2	5.0	0.6 $\pm 0.05$
12.5 ' 20	3.2	0.7	1.2	5.0	0.6 $\pm 0.05$
12.5 ' 25	3.2	0.7	1.2	5.0	0.6 $\pm 0.05$
16 ' 20	3.5	0.7	1.6	7.5	0.8 $\pm 0.05$
16 ' 25	3.5	0.7	1.6	7.5	0.8 $\pm 0.05$
16 ' 31.5	3.5	0.7	1.6	7.5	0.8 $\pm 0.05$
16 ' 35.5	3.5	0.7	1.6	7.5	0.8 $\pm 0.05$
18 ' 20	3.5	0.7	1.6	7.5	0.8 $\pm 0.1$
18 ' 25	3.5	0.7	1.6	7.5	0.8 $\pm 0.1$
18 ' 31.5	3.5	0.7	1.6	7.5	0.8 $\pm 0.1$
18 ' 35	3.5	0.7	1.6	7.5	0.8 $\pm 0.1$


**B41002**

Compact 85 °C

Bent 90 ° leads for horizontal mounting pinning

Last 3 digits of ordering code: 012



Case size d ' l (mm)	Dimensions (mm)				
	C $\pm 0.5$	E $\pm 0.5$	F $\pm 0.5$	a $\pm 0.5$	$A\bar{b}$
16 ' 20	4.0	4.0	12.0	7.5	0.8 $\pm 0.05$
16 ' 25	4.0	4.0	12.0	7.5	0.8 $\pm 0.05$
16 ' 31.5	4.0	4.0	12.0	7.5	0.8 $\pm 0.05$
16 ' 35.5	4.0	4.0	12.0	7.5	0.8 $\pm 0.05$
18 ' 20	4.0	4.0	13.0	7.5	0.8 $\pm 0.1$
18 ' 25	4.0	4.0	13.0	7.5	0.8 $\pm 0.1$
18 ' 31.5	4.0	4.0	13.0	7.5	0.8 $\pm 0.1$
18 ' 35	4.0	4.0	13.0	7.5	0.8 $\pm 0.1$
18 ' 40	4.0	4.0	13.0	7.5	0.8 $\pm 0.1$


Bent leads for diameter 12.5 mm available upon request.



## Packing units and box dimensions

### Ammo pack


Valid for series B41002, B41022, B41044, B41827, B41828, B43044, B43082, B43086, B43088, B43827, B43828.



Case size d ' l mm	Dimensions (mm)			Packing units pcs.
	A <sub>max</sub>	B <sub>max</sub>	C <sub>max</sub>	
4 ' 7	330	50	196	2000
5 ' 7	330	50	226	2000
5 ' 11	330	50	226	2000
6.3 ' 7	330	50	286	2000
6.3 ' 11	330	50	286	2000
8 ' 7	330	50	246	1000
8 ' 11.5	330	50	246	1000
8 ' 15	330	50	246	500
10 ' 12.5	330	50	196	500
10 ' 16	330	54	196	500
10 ' 20	330	58	196	500
12.5 ' 20	341	60	272	500
12.5 ' 25	341	65	272	500
16 ' 25	320	65	270	300
16 ' 31.5	315	65	275	300
18 ' 20	315	65	275	250
18 ' 25	315	65	275	250
18 ' 31.5	315	65	275	250


**B41002**
**Compact 85 °C**
**Ammo pack**

Valid for series B41858, B41859, B41863, B41866, B41868, B41888, B41890, B41896, B42824, B42851, B43866, B43867, B43890, B43896.



Case size d ' l mm	Dimensions (mm)			Packing units pcs.
	A <sub>max</sub>	B <sub>max</sub>	C <sub>max</sub>	
8 ' 11.5	345	55	240	1000
10 ' 12.5	345	55	280	750
10 ' 16	345	60	200	500
10 ' 20	345	60	200	500
12.5 ' 20	345	65	280	500
12.5 ' 25	345	65	280	500
16 ' 20	315	65	275	300
16 ' 25	315	65	275	300
16 ' 31.5	315	65	275	300
18 ' 20	315	65	275	250
18 ' 25	315	65	275	250
18 ' 31.5	315	65	275	250


**Overview of packing units and code numbers for case sizes 4 x 7 ... 16 x 40**

Valid for series B41002, B41022, B41044, B41827, B41828, B43044, B43082, B43086, B43088, B43827, B43828.

Case size d x l mm	Standard, bulk pcs.	Taped, Ammo pack pcs.	Kinked leads, bulk pcs.	Cut leads, bulk pcs.																		
4 x 7	10000	2000	15000	15000																		
5 x 7	7500	2000	10000	10000																		
5 x 11	5000	2000	10000	10000																		
6.3 x 7	5000	2000	10000	10000																		
6.3 x 11	5000	2000	5000	5000																		
8 x 7	5000	1000	5000	5000																		
8 x 11.5	2500	1000	4000	4000																		
8 x 15	2000	1000	2500	2500																		
8 x 20	1500		2000	2000																		
10 x 12.5	2000	500	2500	2500																		
10 x 16	1500	500	2000	2000																		
10 x 20	1000	500	1500	1500																		
10 x 25	1000	500	1250	1250																		
12.5 x 16	750	500	1000	1000																		
12.5 x 20	750	500	500	500																		
12.5 x 25	750	500	500	500																		
12.5 x 31.5	500		750	750																		
12.5 x 35.5	500		750	750																		
12.5 x 40	500		750	750																		
16 x 20	375	300	500	500																		
16 x 25	375	300	500	500																		
16 x 31.5	250	300	375	375																		
16 x 35.5	250		375	375																		
16 x 40	250		375	375																		
The last three digits of the complete ordering code state the lead configuration	000	<table border="1"> <tr> <th>Code</th><th>F (mm)</th><th>d (mm)</th></tr> <tr><td>006</td><td>3.5</td><td>8</td></tr> <tr><td>007</td><td>2.5</td><td>4 ... 6.3</td></tr> <tr><td>008</td><td>5.0</td><td>4 ... 12.5</td></tr> <tr><td>009</td><td>7.5</td><td>16 ... 18</td></tr> <tr><td>016</td><td>2.0</td><td>4 ... 5</td></tr> </table>	Code	F (mm)	d (mm)	006	3.5	8	007	2.5	4 ... 6.3	008	5.0	4 ... 12.5	009	7.5	16 ... 18	016	2.0	4 ... 5	001	002
Code	F (mm)	d (mm)																				
006	3.5	8																				
007	2.5	4 ... 6.3																				
008	5.0	4 ... 12.5																				
009	7.5	16 ... 18																				
016	2.0	4 ... 5																				


**B41002**
**Compact 85 °C**

Overview of packing units and code numbers for case sizes 18 x 20 ... 18 x 40

Valid for series B41002, B41022, B41044, B41827, B41828, B43044, B43082, B43086, B43088, B43827, B43828.

Case size d x l mm	Standard, bulk pcs.	Taped, Ammo pack pcs.	Kinked leads, bulk pcs.	Cut leads, bulk pcs.		
18 x 20	250	250	100	100		
18 x 25	250	250	100	100		
18 x 31.5	250	250	100	100		
18 x 35.5	250		100	100		
18 x 40	250		100	100		
The last three digits of the complete ordering code state the lead configuration	000	Code 009	F (mm) 7.5	d (mm) 16 ... 18	001	002



Overview of packing units and code numbers for case sizes 8 ' 11.5 ... 16 ' 35.5

Valid for series B41858, B41859, B41863, B41866, B41868, B41888, B41890, B41896, B42824, B42851, B43866, B43867, B43890, B43896.

					PAPR				
Case size d ' l mm	Stand- ard, bulk pcs.	Taped, Ammo pack pcs.	Kinked leads, bulk pcs.	Cut leads, bulk pcs.	Crimped leads, blister pcs.	J leads, blister pcs.	Bent 90° leads, blister pcs.		
8 ' 11.5	1000	1000							
10 ' 12.5	1000	750		1000		675			
10 ' 16	1000	500		1000		675			
10 ' 20	500	500	500	500		500			
12.5 ' 20	350	500	350	350		300	<sup>1)</sup>		
12.5 ' 25	250	500	500	500		225	<sup>1)</sup>		
12.5 ' 30	200								
12.5 ' 35	175								
12.5 ' 40	175								
16 ' 20	250	300	200	200	200	200	120		
16 ' 25	250	300	200	200	200	200	120		
16 ' 31.5	200	300	250	250	344	344	120		
16 ' 35.5	100		100	100	150	150	150		
The last three digits of the complete ordering code state the lead configuration	000	Code	F (mm)	d (mm)	001	002	003	004	012
		006	3.5	8					
		008	5	5...12.5					
		009	7.5	16...18					

1) Available upon request


**B41002**

Compact 85 °C

Overview of packing units and code numbers for case sizes 18 ' 20 ... 18 ' 40

Valid for series B41858, B41859, B41863, B41866, B41868, B41888, B41890, B41896, B42824, B42851, B43866, B43867, B43890, B43896.

						PAPR			
Case size d ' l mm	Stand- ard, bulk pcs.	Taped, Ammo pack pcs.		Kinked leads, bulk pcs.	Cut leads, bulk pcs.	Crimped leads, blister pcs.	J leads, blister pcs.	Bent 90° leads, blister pcs.	
18 ' 20	175	250		175	175	200	200	120	
18 ' 25	150	250		150	150	200	200	120	
18 ' 31.5	100	250		100	100	150	150	120	
18 ' 35	100			100	100	150	150	150	
18 ' 40	125			100	100	120		72	
The last three digits of the complete ordering code state the lead configuration	000	Code	F (mm)	d (mm)	001	002	003	004	012
		009	7.5	16...18					



## Cautions and warnings

### Personal safety

The electrolytes used by EPCOS have not only been optimized with a view to the intended application, but also with regard to health and environmental compatibility. They do not contain any solvents that are detrimental to health, e.g. dimethyl formamide (DMF) or dimethyl acetamide (DMAC).

Furthermore, part of the high-voltage electrolytes used by EPCOS are self-extinguishing. They contain flame-retarding substances which will quickly extinguish any flame that may have been ignited.

As far as possible, EPCOS does not use any dangerous chemicals or compounds to produce operating electrolytes. However, in exceptional cases, such materials must be used in order to achieve specific physical and electrical properties because no safe substitute materials are currently known. However, the amount of dangerous materials used in our products has been limited to an absolute minimum. Nevertheless, the following rules should be observed when handling aluminum electrolytic capacitors:

- Any escaping electrolyte should not come into contact with eyes or skin.
- If electrolyte does come into contact with the skin, wash the affected parts immediately with running water. If the eyes are affected, rinse them for 10 minutes with plenty of water. If symptoms persist, seek medical treatment.
- Avoid breathing in electrolyte vapor or mists. Workplaces and other affected areas should be well ventilated. Clothing that has been contaminated by electrolyte must be changed and rinsed in water.


**B41002**

Compact 85 °C

## Product safety

The table below summarizes the safety instructions that must be observed without fail. A detailed description can be found in the relevant sections of chapter "General technical information".

Topic	Safety information	Reference chapter "General technical information"
Polarity	Make sure that polar capacitors are connected with the right polarity.	1 "Basic construction of aluminum electrolytic capacitors"
Reverse voltage	Voltages polarity classes should be prevented by connecting a diode.	3.1.6 "Reverse voltage"
Upper category temperature	Do not exceed the upper category temperature.	7.2 "Maximum permissible operating temperature"
Maintenance	Make periodic inspections of the capacitors. Before the inspection, make sure that the power supply is turned off and carefully discharge the electricity of the capacitors. Do not apply any mechanical stress to the capacitor terminals.	10 "Maintenance"
Mounting position of screw-terminal capacitors	Do not mount the capacitor with the terminals (safety vent) upside down.	11.1. "Mounting positions of capacitors with screw terminals"
Mounting of single-ended capacitors	The internal structure of single-ended capacitors might be damaged if excessive force is applied to the lead wires. Avoid any compressive, tensile or flexural stress. Do not move the capacitor after soldering to PC board. Do not pick up the PC board by the soldered capacitor. Do not insert the capacitor on the PC board with a hole space different to the lead space specified.	11.4 "Mounting considerations for single-ended capacitors"
Robustness of terminals	The following maximum tightening torques must not be exceeded when connecting screw terminals: M5: 2 Nm M6: 2.5 Nm	11.3 "Mounting torques"
Soldering	Do not exceed the specified time or temperature limits during soldering.	11.5 "Soldering"



Topic	Safety information	Reference chapter "General technical information"
Soldering, cleaning agents	Do not allow halogenated hydrocarbons to come into contact with aluminum electrolytic capacitors.	11.6 "Cleaning agents"
Passive flammability	Avoid external energy, such as fire or electricity.	8.1 "Passive flammability"
Active flammability	Avoid overload of the capacitors.	8.2 "Active flammability"
		Reference chapter "Capacitors with screw terminals"
Breakdown strength of insulating sleeves	Do not damage the insulating sleeve, especially when ring clips are used for mounting.	"Screw terminals accessories"



B41002

Compact 85 °C

## Symbols and terms

Symbol	English	German
C	Capacitance	Kapazität
$C_R$	Rated capacitance	Nennkapazität
$C_S$	Series capacitance	Serienkapazität
$C_{S,T}$	Series capacitance at temperature T	Serienkapazität bei Temperatur T
$C_f$	Capacitance at frequency f	Kapazität bei Frequenz f
d	Case diameter, nominal dimension	Gehäusedurchmesser, Nennmaß
$d_{max}$	Maximum case diameter	Maximaler Gehäusedurchmesser
ESL	Self-inductance	Eigeninduktivität
ESR	Equivalent series resistance	Ersatzserienwiderstand
$ESR_f$	Equivalent series resistance at frequency f	Ersatzserienwiderstand bei Frequenz f
$ESR_T$	Equivalent series resistance at temperature T	Ersatzserienwiderstand bei Temperatur T
f	Frequency	Frequenz
I	Current	Strom
$I_{AC}$	Alternating current (ripple current)	Wechselstrom
$I_{AC,rms}$	Root-mean-square value of alternating current	Wechselstrom, Effektivwert
$I_{AC,f}$	Ripple current at frequency f	Wechselstrom bei Frequenz f
$I_{AC,max}$	Maximum permissible ripple current	Maximal zulässiger Wechselstrom
$I_{AC,R}$	Rated ripple current	Nennwechselstrom
$I_{AC,R}$ (B)	Rated ripple current for base cooling	Nennwechselstromstrom für Bodenkühlung
$I_{leak}$	Leakage current	Reststrom
$I_{leak,op}$	Operating leakage current	Betriebsreststrom
l	Case length, nominal dimension	Gehäselänge, Nennmaß
$l_{max}$	Maximum case length (without terminals and mounting stud)	Maximale Gehäselänge (ohne Anschlüsse und Gewindegelenken)
R	Resistance	Widerstand
$R_{ins}$	Insulation resistance	Isolationswiderstand
$R_{symm}$	Balancing resistance	Symmetrierwiderstand
T	Temperature	Temperatur
DT	Temperature difference	Temperaturdifferenz
$T_A$	Ambient temperature	Umgebungstemperatur
$T_C$	Case temperature	Gehäsetemperatur
$T_B$	Capacitor base temperature	Temperatur des Becherbodens
t	Time	Zeit
Dt	Period	Zeitraum
$t_b$	Service life (operating hours)	Brauchbarkeitsdauer (Betriebszeit)



Symbol	English	German
V	Voltage	Spannung
$V_F$	Forming voltage	Formierspannung
$V_{op}$	Operating voltage	Betriebsspannung
$V_R$	Rated voltage, DC voltage	Nennspannung, Gleichspannung
$V_s$	Surge voltage	Spitzenspannung
$X_C$	Capacitive reactance	Kapazitiver Blindwiderstand
$X_L$	Inductive reactance	Induktiver Blindwiderstand
Z	Impedance	Scheinwiderstand
$Z_T$	Impedance at temperature T	Scheinwiderstand bei Temperatur T
$\tan \delta$	Dissipation factor	Verlustfaktor
I	Failure rate	Ausfallrate
$\epsilon_0$	Absolute permittivity	Elektrische Feldkonstante
$\epsilon_r$	Relative permittivity	Dielektrizitätszahl
w	Angular velocity; 2 p f	Kreisfrequenz; 2 p f

#### Note

All dimensions are given in mm.

The following applies to all products named in this publication:

1. Some parts of this publication contain statements about the suitability of our products for certain areas of application . These statements are based on our knowledge of typical requirements that are often placed on our products in the areas of application concerned. We nevertheless expressly point out that such statements cannot be regarded as binding statements about the suitability of our products for a particular customer application . As a rule, EPCOS is either unfamiliar with individual customer applications or less familiar with them than the customers themselves. For these reasons, it is always ultimately incumbent on the customer to check and decide whether an EPCOS product with the properties described in the product specification is suitable for use in a particular customer application.
2. We also point out that in individual cases, a malfunction of electronic components or failure before the end of their usual service life cannot be completely ruled out in the current state of the art, even if they are operated as specified . In customer applications requiring a very high level of operational safety and especially in customer applications in which the malfunction or failure of an electronic component could endanger human life or health (e.g. in accident prevention or lifesaving systems), it must therefore be ensured by means of suitable design of the customer application or other action taken by the customer (e.g. installation of protective circuitry or redundancy) that no injury or damage is sustained by third parties in the event of malfunction or failure of an electronic component.
3. The warnings, cautions and product-specific notes must be observed.
4. In order to satisfy certain technical requirements, some of the products described in this publication may contain substances subject to restrictions in certain jurisdictions (e.g. because they are classed as hazardous) . Useful information on this will be found in our Material Data Sheets on the Internet ([www.epcos.com/material](http://www.epcos.com/material)). Should you have any more detailed questions, please contact our sales offices.
5. We constantly strive to improve our products. Consequently, the products described in this publication may change from time to time . The same is true of the corresponding product specifications. Please check therefore to what extent product descriptions and specifications contained in this publication are still applicable before or when you place an order. We also reserve the right to discontinue production and delivery of products . Consequently, we cannot guarantee that all products named in this publication will always be available. The aforementioned does not apply in the case of individual agreements deviating from the foregoing for customer-specific products.
6. Unless otherwise agreed in individual contracts, all orders are subject to the current version of the "General Terms of Delivery for Products and Services in the Electrical Industry" published by the German Electrical and Electronics Industry Association (ZVEI).
7. The trade names EPCOS, BAOKE, Alu-X, CeraDiode, CSMP, CSSP, CTVS, DeltaCap, DigiSiMic, DSSP, FormFit, MiniBlue, MiniCell, MKK, MKD, MLSC, MotorCap, PCC, PhaseCap, PhaseCube, PhaseMod, PhiCap, SIFERRIT, SIFI, SIKOREL, SilverCap, SIMDAD, SiMic, SIMID, SineFormer, SIOV, SIP5D, SIP5K, ThermoFuse, WindCap are trademarks registered or pending in Europe and in other countries. Further information will be found on the Internet at [www.epcos.com/trademarks](http://www.epcos.com/trademarks).