



Aluminum electrolytic capacitors

Single-ended capacitors

Series/Type: B41821, B43821
Date: December 2010

General-purpose grade capacitors

Applications

- General-purpose applications in the entertainment industry
- Semi-professional to professional application range
- For filtering, coupling and pulse circuits

Features

- Compact dimensions
- High CV product, i.e. very compact
- RoHS-compatible

Construction


- Radial leads
- Charge-discharge proof, polar
- Aluminum case with insulating sleeve
- Minus pole marking on the insulating sleeve
- Case with safety vent from diameter 6.3 mm

Delivery mode

Terminal configurations and packing:

- Bulk
- Taped, Ammo pack
- Cut (see chapter "Single-ended Taping, packing and lead configurations, Cut leads (Chapter B)")
- Kinked (see chapter "Single-ended Taping, packing and lead configurations, Kinked leads (Chapter B)")
- PAPR (protection against polarity reversal):
crimped leads, J leads, bent leads

Refer to chapter "Single-ended capacitors Taping, packing and lead configurations" for further details.





Specifications and characteristics in brief

Series	B41821					B43821				
Rated voltage V_R	6.3 ... 100 V DC					160 ... 450 V DC				
Surge voltage V_S	1.15 V_R					1.1 V_R				
Rated capacitance C_R	0.1 ... 10000 μ F					0.47 ... 680 μ F				
Capacitance tolerance	\pm 20% M					\pm 20% M				
Dissipation factor tan d (20 °C, 120 Hz)	For capacitance higher than 1000 μ F add 0.02 for every increase of 1000 μ F.									
	V_R (V DC)	6.3	10	16	25	35	50	63	100	160 ... 450
	tan d (max.)	0.28	0.24	0.20	0.16	0.14	0.12	0.12	0.10	0.20
Leakage current I_{leak} (20 °C, 5 min)	$I_{leak} = 0.01 \mu A \cdot \left(\frac{C_R}{\mu F} \cdot \frac{V_R}{V} \right)$ or 3 μA , whichever is greater					$I_{leak} = 0.03 \mu A \cdot \left(\frac{C_R}{\mu F} \cdot \frac{V_R}{V} \right) + 15 \mu A$				
Self-inductance ESL	Diameter (mm)	£ 6.3		8 ... 12.5		16		18		20 ... 25
	ESL (nH)	15		20		26		34		40
Useful life 85 °C; V_R ; $I_{AC,R}$ 40 °C; V_R ; 1.3 $I_{AC,R}$ 40 °C; V_R ; 1.6 $I_{AC,R}$	> 2000 h > 100000 h					> 3000 h > 100000 h				
Requirements	DC/C £ \pm 45% of initial value tan d £ 3 times initial specified limit I_{leak} £ initial specified limit									
Voltage endurance test 85 °C; V_R	2000 h					2000 h				
Post test requirements	DC/C £ \pm 30% of initial value tan d £ 2 times initial specified limit I_{leak} £ initial specified limit									
Vibration resistance test	To IEC 60068-2-6, test Fc: Frequency range 10 Hz ... 2 kHz, displacement amplitude 1.5 mm, acceleration max. 20 g, duration 3 ´ 2 h. Capacitor rigidly clamped by the aluminum case.									
IEC climatic category	To IEC 60068-1: V_R £ 250 V: 40/085/56 (40 °C/+85 °C/56 days damp heat test) V_R £ 350 V: 25/085/56 (25 °C/+85 °C/56 days damp heat test)									
Sectional specification	IEC 60384-4									



B41821, B43821


Standard series 85 °C

Dimensional drawings

With stand-off rubber seal

Diameters (mm):


6.3, 10, 12.5, 16, 18, 22, 25



With flat rubber seal

Diameters (mm):

5, 8, 20



Safety vent for diameter ³ 6.3 mm.

Dimensions and weights

Dimensions (mm)				Approx. weight
d +0.5	l	a ±0.5	b	g
5	11 +1.0	2.0	0.50 ±0.05	0.5
6.3	11 +1.0	2.5	0.50 ±0.05	0.7
8	11.5 +1.5	3.5	0.60 ±0.05	1.0
10	12.5 +1.0	5.0	0.60 ±0.05	1.6
10	16 +1.0	5.0	0.60 ±0.05	1.9
10	20 +2.0	5.0	0.60 ±0.05	2.6
12.5	20 +2.0	5.0	0.60 ±0.05	3.6
12.5	25 +2.0	5.0	0.60 ±0.05	4.5
16	20 +2.0	7.5	0.80 ±0.05	5.5
16	25 +2.0	7.5	0.80 ±0.05	7.5
16	31.5 +2.0	7.5	0.80 ±0.05	7.8
18	31.5 +2.0	7.5	0.80 ±0.1	11.0
18	35 +2.0	7.5	0.80 ±0.1	13.0
18	40 +2.0	7.5	0.80 ±0.1	16.0
20	30 +2.0	10.0	1.0 ±0.1	14.0
20	35 +2.0	10.0	1.0 ±0.1	18.0
20	40 +2.0	10.0	1.0 ±0.1	20.0
22	40 +2.0	10.0	1.0 ±0.1	23.0
25	40 +2.0	12.5	1.0 ±0.1	25.0



Overview of available types B41821

Other voltage and capacitance ratings are available upon request.

V _R (V DC)	6.3	10	16	25	35
	Case dimensions d × l (mm)				
C _R (nF)					
33					5 × 11
47				5 × 11	5 × 11
68				5 × 11	6.3 × 11
100		5 × 11	5 × 11	6.3 × 11	6.3 × 11
220		6.3 × 11	6.3 × 11	8 × 11.5	8 × 11.5
330	6.3 × 11	8 × 11.5	8 × 11.5	8 × 11.5 10 × 12.5	10 × 12.5
470	8 × 11.5	8 × 11.5	8 × 11.5	10 × 12.5	10 × 16
680	8 × 11.5	10 × 12.5	10 × 12.5	10 × 16	10 × 20
1000	10 × 12.5	10 × 12.5	10 × 16	10 × 20	12.5 × 20
1500	10 × 16	10 × 20	10 × 20	12.5 × 20	16 × 20
2200	10 × 20	10 × 20	12.5 × 20	12.5 × 25	16 × 25
3300	10 × 20	12.5 × 25	12.5 × 25 16 × 25	16 × 25	16 × 31.5
4700	12.5 × 25	16 × 20	16 × 25	16 × 31.5	18 × 35
6800		16 × 25	16 × 31.5	18 × 35	18 × 40
10000		18 × 31.5	18 × 35	20 × 40	



B41821

Standard series 85 °C

V _R (V DC)	50	63	100
	Case dimensions d × l (mm)		
C _R (nF)			
0.10			5 × 11
0.22			5 × 11
0.33			5 × 11
0.47			5 × 11
0.68			5 × 11
1.0			5 × 11
2.2			5 × 11
3.3			5 × 11
4.7			5 × 11
10	5 × 11	5 × 11	6.3 × 11
22	5 × 11	5 × 11	8 × 11.5
33	6.3 × 11	6.3 × 11	8 × 11.5 10 × 12.5
47	6.3 × 11	6.3 × 11	10 × 12.5
68	6.3 × 11	8 × 11.5	10 × 16
100	8 × 11.5	8 × 11.5	10 × 20
220	10 × 12.5	10 × 16	12.5 × 25
330	10 × 16	10 × 20	16 × 25
470	10 × 20	12.5 × 20	16 × 31.5
680	12.5 × 20	16 × 20	18 × 40
1000	12.5 × 25	16 × 25	18 × 40 20 × 40
1500	16 × 25	18 × 31.5	
2200	16 × 31.5	18 × 35	
3300	18 × 35	20 × 40	
4700	20 × 40	25 × 40	



Overview of available types B43821

Other voltage and capacitance ratings are available upon request.

V _R (V DC)	160	200	250	350	400	450
	Case dimensions d ´ l (mm)					
C _R (nF)						
0.47			6.3 ´ 11	6.3 ´ 11		
0.68			6.3 ´ 11	6.3 ´ 11		
1.0	6.3 ´ 11	6.3 ´ 11	6.3 ´ 11	6.3 ´ 11		
2.2	6.3 ´ 11	6.3 ´ 11	6.3 ´ 11	6.3 ´ 11 8 ´ 11.5	8 ´ 11.5	8 ´ 11.5
3.3	6.3 ´ 11	6.3 ´ 11	6.3 ´ 11	8 ´ 11.5	8 ´ 11.5	10 ´ 12.5
4.7	6.3 ´ 11	6.3 ´ 11	8 ´ 11.5	8 ´ 11.5	10 ´ 12.5	10 ´ 12.5
10	8 ´ 11.5	8 ´ 11.5	10 ´ 12.5	10 ´ 16	10 ´ 20	10 ´ 20
22	10 ´ 12.5 10 ´ 16	10 ´ 16	10 ´ 20	12.5 ´ 20	12.5 ´ 25	12.5 ´ 25
33	10 ´ 16 10 ´ 20	10 ´ 20	12.5 ´ 20	12.5 ´ 25	16 ´ 20	16 ´ 25
47	10 ´ 20 12.5 ´ 20	12.5 ´ 20	12.5 ´ 25	16 ´ 25	16 ´ 25	16 ´ 31.5
68	12.5 ´ 20	12.5 ´ 25	16 ´ 25	16 ´ 31.5	18 ´ 31.5	18 ´ 35
100	12.5 ´ 25 16 ´ 25	16 ´ 25	16 ´ 31.5	18 ´ 35	18 ´ 40	20 ´ 40
220	16 ´ 31.5 18 ´ 31.5	18 ´ 31.5	18 ´ 40			
330	18 ´ 35	20 ´ 35	22 ´ 40			
470	20 ´ 40	22 ´ 40				
680	25 ´ 40					



B41821

Standard series 85 °C

Technical data and ordering codes B41821

C_R 120 Hz 20 °C nF	Case dimensions d ´ l mm	ESR_{max} 120 Hz 20 °C W	$I_{AC,R}$ 120 Hz 85 °C mA	Ordering code (composition see below)
--------------------------------	--------------------------------	-------------------------------------	-------------------------------------	--

$V_R = 6.3 \text{ V DC}$

330	6.3 ´ 11	1.4	280	B41821A2337M***
470	8 ´ 11.5	1.0	380	B41821B2477M***
680	8 ´ 11.5	0.68	400	B41821F2687M***
1000	10 ´ 12.5	0.46	650	B41821A2108M***
1500	10 ´ 16	0.31	750	B41821A2158M***
2200	10 ´ 20	0.23	1000	B41821A2228M***
3300	10 ´ 20	0.16	1190	B41821A2338M***
4700	12.5 ´ 25	0.12	1600	B41821A2478M***

$V_R = 10 \text{ V DC}$

100	5 ´ 11	4.0	145	B41821A3107M***
220	6.3 ´ 11	1.8	240	B41821A3227M***
330	8 ´ 11.5	1.2	290	B41821B3337M***
470	8 ´ 11.5	0.85	400	B41821A3477M***
680	10 ´ 12.5	0.59	460	B41821A3687M***
1000	10 ´ 12.5	0.40	650	B41821A3108M***
1500	10 ´ 20	0.27	740	B41821A3158M***
2200	10 ´ 20	0.20	1100	B41821A3228M***
3300	12.5 ´ 25	0.14	1550	B41821A3338M***
4700	16 ´ 20	0.11	1700	B41821A3478M***
6800	16 ´ 25	0.08	2250	B41821F3688M***
10000	18 ´ 31.5	0.07	2600	B41821F3109M***

$V_R = 16 \text{ V DC}$

100	5 ´ 11	3.3	180	B41821A4107M***
220	6.3 ´ 11	1.5	260	B41821F4227M***
330	8 ´ 11.5	1.0	370	B41821B4337M***
470	8 ´ 11.5	0.71	440	B41821F4477M***

Composition of ordering code

*** = Version

000 = for standard leads, bulk

001 = for kinked leads, bulk (from d ´ l = 10 ´ 20 mm to 18 ´ 40 mm)

002 = for cut leads, bulk (from d ´ l = 10 ´ 12.5 mm to 22 ´ 40 mm)

003 = for crimped leads, blister (from d ´ l = 16 ´ 20 mm to 20 ´ 40 mm)

004 = for J leads, blister (from d ´ l = 10 ´ 12.5 mm to 18 ´ 35 mm)

006 = for taped leads, Ammo pack, lead spacing F = 3.5 mm (for d = 8 mm)

007 = for taped leads, Ammo pack, lead spacing F = 2.5 mm (from d = 5 mm to 6.3 mm)

008 = for taped leads, Ammo pack, lead spacing F = 5.0 mm (from d ´ l = 5 ´ 11 mm to 12.5 ´ 25 mm)

009 = for taped leads, Ammo pack, lead spacing F = 7.5 mm (for d ´ l = 16 ´ 20 ... 16 ´ 31.5 mm and 18 ´ 25 ... 18 ´ 31.5 mm)

012 = for bent 90° leads, blister (for Æ16 and 18 mm)



B41821

Standard series 85 °C

Technical data and ordering codes B41821

C_R	Case dimensions	ESR_{max}	$I_{AC,R}$	Ordering code
120 Hz	d ´ l	120 Hz	120 Hz	(composition see below)
20 °C	mm	20 °C	85 °C	
nF		W	mA	

 $V_R = 16 \text{ V DC}$

680	10 ´ 12.5	0.49	600	B41821F4687M***
1000	10 ´ 16	0.33	790	B41821A4108M***
1500	10 ´ 20	0.22	950	B41821F4158M***
2200	12.5 ´ 20	0.17	1300	B41821K4228M***
3300	12.5 ´ 25	0.12	1700	B41821F4338M***
3300	16 ´ 25	0.12	1800	B41821A4338M***
4700	16 ´ 25	0.09	2100	B41821A4478M***
6800	16 ´ 31.5	0.07	2300	B41821F4688M***
10000	18 ´ 35	0.06	2750	B41821F4109M***

 $V_R = 25 \text{ V DC}$

47	5 ´ 11	5.6	115	B41821A5476M***
68	5 ´ 11	3.9	125	B41821F5686M***
100	6.3 ´ 11	2.7	190	B41821A5107M***
220	8 ´ 11.5	1.2	330	B41821B5227M***
330	8 ´ 11.5	0.80	440	B41821F5337M***
330	10 ´ 12.5	0.80	440	B41821A5337M***
470	10 ´ 12.5	0.56	550	B41821B5477M***
680	10 ´ 16	0.39	630	B41821F5687M***
1000	10 ´ 20	0.27	960	B41821A5108M***
1500	12.5 ´ 20	0.18	1100	B41821F5158M***
2200	12.5 ´ 25	0.14	1550	B41821F5228M***
3300	16 ´ 25	0.10	1980	B41821A5338M***
4700	16 ´ 31.5	0.08	2450	B41821A5478M***
6800	18 ´ 35	0.06	2650	B41821F5688M***
10000	20 ´ 40	0.06	2900	B41821F5109M***

Composition of ordering code

*** = Version

000 = for standard leads, bulk

001 = for kinked leads, bulk (from d ´ l = 10 ´ 20 mm to 18 ´ 40 mm)

002 = for cut leads, bulk (from d ´ l = 10 ´ 12.5 mm to 22 ´ 40 mm)

003 = for crimped leads, blister (from d ´ l = 16 ´ 20 mm to 20 ´ 40 mm)

004 = for J leads, blister (from d ´ l = 10 ´ 12.5 mm to 18 ´ 35 mm)

006 = for taped leads, Ammo pack, lead spacing F = 3.5 mm (for d = 8 mm)

007 = for taped leads, Ammo pack, lead spacing F = 2.5 mm (from d = 5 mm to 6.3 mm)

008 = for taped leads, Ammo pack, lead spacing F = 5.0 mm (from d ´ l = 5 ´ 11 mm to 12.5 ´ 25 mm)

009 = for taped leads, Ammo pack, lead spacing F = 7.5 mm (for d ´ l = 16 ´ 20 ... 16 ´ 31.5 mm and 18 ´ 25 ... 18 ´ 31.5 mm)

012 = for bent 90° leads, blister (for Æ16 and 18 mm)

**B41821**

Standard series 85 °C

Technical data and ordering codes B41821

C_R 120 Hz 20 °C nF	Case dimensions $d \times l$ mm	ESR_{max} 120 Hz 20 °C W	$I_{AC,R}$ 120 Hz 85 °C mA	Ordering code (composition see below)
$V_R = 35 \text{ V DC}$				
33	5 × 11	7.0	105	B41821A7336M***
47	5 × 11	4.9	130	B41821A7476M***
68	6.3 × 11	3.4	160	B41821A7686M***
100	6.3 × 11	2.3	210	B41821F7107M***
220	8 × 11.5	1.1	385	B41821F7227M***
330	10 × 12.5	0.70	490	B41821A7337M***
470	10 × 16	0.49	650	B41821A7477M***
680	10 × 20	0.34	840	B41821A7687M***
1000	12.5 × 20	0.23	1150	B41821K7108M***
1500	16 × 20	0.15	1400	B41821F7158M***
2200	16 × 25	0.12	1800	B41821F7228M***
3300	16 × 31.5	0.09	2100	B41821F7338M***
4700	18 × 35	0.07	2550	B41821F7478M***
6800	18 × 40	0.06	2800	B41821K7688M***
$V_R = 50 \text{ V DC}$				
10	5 × 11	20	60	B41821A6106M***
22	5 × 11	9.0	95	B41821A6226M***
33	6.3 × 11	6.0	110	B41821A6336M***
47	6.3 × 11	4.2	155	B41821A6476M***
68	6.3 × 11	2.9	210	B41821F6686M***
100	8 × 11.5	2.0	260	B41821A6107M***
220	10 × 12.5	0.90	430	B41821A6227M***
330	10 × 16	0.60	590	B41821A6337M***

Composition of ordering code

*** = Version

000 = for standard leads, bulk

001 = for kinked leads, bulk (from $d \times l = 10 \times 20$ mm to 18×40 mm)002 = for cut leads, bulk (from $d \times l = 10 \times 12.5$ mm to 22×40 mm)003 = for crimped leads, blister (from $d \times l = 16 \times 20$ mm to 20×40 mm)004 = for J leads, blister (from $d \times l = 10 \times 12.5$ mm to 18×35 mm)006 = for taped leads, Ammo pack, lead spacing $F = 3.5$ mm (for $d = 8$ mm)007 = for taped leads, Ammo pack, lead spacing $F = 2.5$ mm (from $d = 5$ mm to 6.3 mm)008 = for taped leads, Ammo pack, lead spacing $F = 5.0$ mm (from $d \times l = 5 \times 11$ mm to 12.5×25 mm)009 = for taped leads, Ammo pack, lead spacing $F = 7.5$ mm (for $d \times l = 16 \times 20 \dots 16 \times 31.5$ mm and $18 \times 25 \dots 18 \times 31.5$ mm)012 = for bent 90° leads, blister (for $\varnothing 16$ and 18 mm)



B41821

Standard series 85 °C

Technical data and ordering codes B41821

C_R 120 Hz 20 °C nF	Case dimensions $d \times l$ mm	ESR_{max} 120 Hz 20 °C W	$I_{AC,R}$ 120 Hz 85 °C mA	Ordering code (composition see below)
$V_R = 50 \text{ V DC}$				
470	10 × 20	0.42	760	B41821A6477M***
680	12.5 × 20	0.29	1000	B41821F6687M***
1000	12.5 × 25	0.20	1350	B41821F6108M***
1500	16 × 25	0.13	1800	B41821F6158M***
2200	16 × 31.5	0.11	1980	B41821F6228M***
3300	18 × 35	0.08	2500	B41821F6338M***
4700	20 × 40	0.06	2800	B41821K6478M***
$V_R = 63 \text{ V DC}$				
10	5 × 11	20	65	B41821A8106M***
22	5 × 11	9.0	100	B41821F8226M***
33	6.3 × 11	6.0	140	B41821A8336M***
47	6.3 × 11	4.2	170	B41821F8476M***
68	8 × 11.5	2.9	220	B41821F8686M***
100	8 × 11.5	2.0	280	B41821F8107M***
220	10 × 16	0.90	490	B41821A8227M***
330	10 × 20	0.60	710	B41821A8337M***
470	12.5 × 20	0.42	900	B41821F8477M***
680	16 × 20	0.29	1100	B41821F8687M***
1000	16 × 25	0.20	1300	B41821F8108M***
1500	18 × 31.5	0.13	1800	B41821F8158M***
2200	18 × 35	0.11	2300	B41821K8228M***
3300	20 × 40	0.08	2700	B41821A8338M***
4700	25 × 40	0.06	3200	B41821F8478M***

Composition of ordering code

*** = Version

000 = for standard leads, bulk

001 = for kinked leads, bulk (from $d \times l = 10 \times 20$ mm to 18×40 mm)

002 = for cut leads, bulk (from $d \times l = 10 \times 12.5$ mm to 22×40 mm)

003 = for crimped leads, blister (from $d \times l = 16 \times 20$ mm to 20×40 mm)

004 = for J leads, blister (from $d \times l = 10 \times 12.5$ mm to 18×35 mm)

006 = for taped leads, Ammo pack, lead spacing $F = 3.5$ mm (for $d = 8$ mm)

007 = for taped leads, Ammo pack, lead spacing $F = 2.5$ mm (from $d = 5$ mm to 6.3 mm)

008 = for taped leads, Ammo pack, lead spacing $F = 5.0$ mm (from $d \times l = 5 \times 11$ mm to 12.5×25 mm)

009 = for taped leads, Ammo pack, lead spacing $F = 7.5$ mm (for $d \times l = 16 \times 20 \dots 16 \times 31.5$ mm and $18 \times 25 \dots 18 \times 31.5$ mm)

012 = for bent 90° leads, blister (for $\varnothing 16$ and 18 mm)



B41821

Standard series 85 °C

Technical data and ordering codes B41821

C_R 120 Hz 20 °C nF	Case dimensions d ´ l mm	ESR _{max} 120 Hz 20 °C W	I _{AC,R} 120 Hz 85 °C mA	Ordering code (composition see below)
$V_R = 100 \text{ V DC}$				
0.1	5 ´ 11	1658	2	B41821A9104M***
0.22	5 ´ 11	754	5	B41821A9224M***
0.33	5 ´ 11	502	7	B41821A9334M***
0.47	5 ´ 11	353	10	B41821A9474M***
0.68	5 ´ 11	244	13	B41821A9684M***
1	5 ´ 11	166	21	B41821A9105M***
2.2	5 ´ 11	75	30	B41821A9225M***
3.3	5 ´ 11	50	40	B41821A9335M***
4.7	5 ´ 11	35	45	B41821A9475M***
10	6.3 ´ 11	17	75	B41821A9106M***
22	8 ´ 11.5	7.5	140	B41821B9226M***
33	8 ´ 11.5	5.0	180	B41821F9336M***
33	10 ´ 12.5	5.0	190	B41821A9336M***
47	10 ´ 12.5	3.5	230	B41821B9476M***
68	10 ´ 16	2.4	280	B41821A9686M***
100	10 ´ 20	1.7	350	B41821A9107M***
220	12.5 ´ 25	0.75	620	B41821A9227M***
330	16 ´ 25	0.50	800	B41821A9337M***
470	16 ´ 31.5	0.35	1000	B41821A9477M***
680	18 ´ 40	0.24	1100	B41821F9687M***
1000	18 ´ 40	0.17	1300	B41821G9108M***
1000	20 ´ 40	0.17	1400	B41821A9108M***

Composition of ordering code

*** = Version

000 = for standard leads, bulk

001 = for kinked leads, bulk (from d ´ l = 10 ´ 20 mm to 18 ´ 40 mm)

002 = for cut leads, bulk (from d ´ l = 10 ´ 12.5 mm to 22 ´ 40 mm)

003 = for crimped leads, blister (from d ´ l = 16 ´ 20 mm to 20 ´ 40 mm)

004 = for J leads, blister (from d ´ l = 10 ´ 12.5 mm to 18 ´ 35 mm)

006 = for taped leads, Ammo pack, lead spacing F = 3.5 mm (for d = 8 mm)

007 = for taped leads, Ammo pack, lead spacing F = 2.5 mm (from d = 5 mm to 6.3 mm)

008 = for taped leads, Ammo pack, lead spacing F = 5.0 mm (from d ´ l = 5 ´ 11 mm to 12.5 ´ 25 mm)

009 = for taped leads, Ammo pack, lead spacing F = 7.5 mm (for d ´ l = 16 ´ 20 ... 16 ´ 31.5 mm and 18 ´ 25 ... 18 ´ 31.5 mm)

012 = for bent 90° leads, blister (for Æ 16 and 18 mm)



Technical data and ordering codes B43821

C _R 120 Hz 20 °C nF	Case dimensions d × l mm	ESR _{max} 120 Hz 20 °C W	I _{AC,R} 120 Hz 85 °C mA	Ordering code (composition see below)
V _R = 160 V DC				
1	6.3 × 11	186	22	B43821A1105M***
2.2	6.3 × 11	85	33	B43821A1225M***
3.3	6.3 × 11	56	40	B43821A1335M***
4.7	6.3 × 11	40	50	B43821F1475M***
10	8 × 11.5	18	80	B43821G1106M***
22	10 × 12.5	13	130	B43821F1226M***
22	10 × 16	8.4	155	B43821A1226M***
33	10 × 16	7.5	180	B43821F1336M***
33	10 × 20	5.6	205	B43821A1336M***
47	10 × 20	4.9	210	B43821K1476M***
47	12.5 × 20	4.5	270	B43821F1476M***
68	12.5 × 20	3.0	350	B43821K1686M***
100	12.5 × 25	2.3	430	B43821F1107M***
100	16 × 25	1.8	475	B43821A1107M***
220	16 × 31.5	1.0	760	B43821F1227M***
220	18 × 31.5	0.84	800	B43821A1227M***
330	18 × 35	0.70	995	B43821F1337M***
470	20 × 40	0.42	1300	B43821F1477M***
680	25 × 40	0.34	1500	B43821F1687M***
V _R = 200 V DC				
1	6.3 × 11	186	22	B43821A2105M***
2.2	6.3 × 11	85	33	B43821A2225M***
3.3	6.3 × 11	56	40	B43821A2335M***
4.7	6.3 × 11	40	50	B43821R2475M***
10	8 × 11.5	21	80	B43821G2106M***
22	10 × 16	8.4	155	B43821B2226M***

Composition of ordering code

*** = Version

000 = for standard leads, bulk

001 = for kinked leads, bulk (from d × l = 10 × 20 mm to 22 × 40 mm)

002 = for cut leads, bulk (from d × l = 10 × 12.5 mm to 22 × 40 mm)

003 = for crimped leads, blister (from d × l = 16 × 20 mm to 20 × 40 mm)

004 = for J leads, blister (from d × l = 10 × 12.5 mm to 18 × 35 mm)

006 = for taped leads, Ammo pack, lead spacing F = 3.5 mm (for d = 8 mm)

007 = for taped leads, Ammo pack, lead spacing F = 2.5 mm (from d = 5 mm to 6.3 mm)

008 = for taped leads, Ammo pack, lead spacing F = 5.0 mm (from d × l = 5 × 11 mm to 12.5 × 25 mm)

009 = for taped leads, Ammo pack, lead spacing F = 7.5 mm (for d × l = 16 × 20 ... 16 × 31.5 mm and 18 × 25 ... 18 × 31.5 mm)

012 = for bent 90° leads, blister (for Æ16 and 18 mm)



B43821

Standard series 85 °C

Technical data and ordering codes B43821

C_R 120 Hz 20 °C nF	Case dimensions d ´ l mm	ESR _{max} 120 Hz 20 °C W	I _{AC,R} 120 Hz 85 °C mA	Ordering code (composition see below)
$V_R = 200 \text{ V DC}$				
33	10 ´ 20	5.6	205	B43821B2336M***
47	12.5 ´ 20	4.5	270	B43821B2476M***
68	12.5 ´ 25	3.3	350	B43821B2686M***
100	16 ´ 25	1.8	475	B43821A2107M***
220	18 ´ 31.5	0.95	690	B43821B2227M***
330	20 ´ 35	0.65	950	B43821R2337M***
470	22 ´ 40	0.46	1300	B43821R2477M***
$V_R = 250 \text{ V DC}$				
0.47	6.3 ´ 11	395	15	B43821F2474M***
0.68	6.3 ´ 11	273	18	B43821F2684M***
1	6.3 ´ 11	186	22	B43821F2105M***
2.2	6.3 ´ 11	85	33	B43821F2225M***
3.3	6.3 ´ 11	65	40	B43821K2335M***
4.7	8 ´ 11.5	40	55	B43821K2475M***
10	10 ´ 12.5	23	95	B43821K2106M***
22	10 ´ 20	8.4	170	B43821F2226M***
33	12.5 ´ 20	5.6	230	B43821K2336M***
47	12.5 ´ 25	4.3	290	B43821K2476M***
68	16 ´ 25	2.7	380	B43821F2686M***
100	16 ´ 31.5	1.8	520	B43821K2107M***
220	18 ´ 40	0.84	680	B43821F2227M***
330	22 ´ 40	0.56	940	B43821F2337M***

Composition of ordering code

*** = Version

000 = for standard leads, bulk

001 = for kinked leads, bulk (from d ´ l = 10 ´ 20 mm to 18 ´ 40 mm)

002 = for cut leads, bulk (from d ´ l = 10 ´ 12.5 mm to 22 ´ 40 mm)

003 = for crimped leads, blister (from d ´ l = 16 ´ 20 mm to 20 ´ 40 mm)

004 = for J leads, blister (from d ´ l = 10 ´ 12.5 mm to 18 ´ 35 mm)

006 = for taped leads, Ammo pack, lead spacing F = 3.5 mm (for d = 8 mm)

007 = for taped leads, Ammo pack, lead spacing F = 2.5 mm (from d = 5 mm to 6.3 mm)

008 = for taped leads, Ammo pack, lead spacing F = 5.0 mm (from d ´ l = 5 ´ 11 mm to 12.5 ´ 25 mm)

009 = for taped leads, Ammo pack, lead spacing F = 7.5 mm (for d ´ l = 16 ´ 20 ... 16 ´ 31.5 mm and 18 ´ 25 ... 18 ´ 31.5 mm)

012 = for bent 90° leads, blister (for Æ16 and 18 mm)



Technical data and ordering codes B43821

C_R 120 Hz 20 °C nF	Case dimensions d × l mm	ESR_{max} 120 Hz 20 °C W	$I_{AC,R}$ 120 Hz 85 °C mA	Ordering code (composition see below)
$V_R = 350 \text{ V DC}$				
0.47	6.3 × 11	395	15	B43821A4474M***
0.68	6.3 × 11	273	18	B43821A4684M***
1	6.3 × 11	186	22	B43821A4105M***
2.2	6.3 × 11	97	30	B43821F4225M***
2.2	8 × 11.5	85	38	B43821B4225M***
3.3	8 × 11.5	65	43	B43821F4335M***
4.7	8 × 11.5	45	55	B43821F4475M***
10	10 × 16	21	90	B43821F4106M***
22	12.5 × 20	9.0	170	B43821F4226M***
33	12.5 × 25	5.6	240	B43821F4336M***
47	16 × 25	4.0	300	B43821F4476M***
68	16 × 31.5	3.1	400	B43821F4686M***
100	18 × 35	2.3	520	B43821F4107M***
$V_R = 400 \text{ V DC}$				
2.2	8 × 11.5	97	38	B43821F9225M***
3.3	8 × 11.5	65	48	B43821F9335M***
4.7	10 × 12.5	46	60	B43821F9475M***
10	10 × 20	18	115	B43821A9106M***
22	12.5 × 25	8.4	200	B43821F9226M***
33	16 × 20	5.6	240	B43821F9336M***
47	16 × 25	4.0	280	B43821F9476M***
68	18 × 31.5	2.8	420	B43821A9686M***
100	18 × 40	1.9	450	B43821F9107M***

Composition of ordering code

*** = Version

000 = for standard leads, bulk

001 = for kinked leads, bulk (from d × l = 10 × 20 mm to 18 × 40 mm)

002 = for cut leads, bulk (from d × l = 10 × 12.5 mm to 22 × 40 mm)

003 = for crimped leads, blister (from d × l = 16 × 20 mm to 20 × 40 mm)

004 = for J leads, blister (from d × l = 10 × 12.5 mm to 18 × 35 mm)

006 = for taped leads, Ammo pack, lead spacing F = 3.5 mm (for d = 8 mm)

007 = for taped leads, Ammo pack, lead spacing F = 2.5 mm (from d = 5 mm to 6.3 mm)

008 = for taped leads, Ammo pack, lead spacing F = 5.0 mm (from d × l = 5 × 11 mm to 12.5 × 25 mm)

009 = for taped leads, Ammo pack, lead spacing F = 7.5 mm (for d × l = 16 × 20 ... 16 × 31.5 mm and 18 × 25 ... 18 × 31.5 mm)

012 = for bent 90° leads, blister (for \varnothing 16 and 18 mm)



B43821

Standard series 85 °C

Technical data and ordering codes B43821

C_R 120 Hz 20 °C nF	Case dimensions d ´ l mm	ESR_{max} 120 Hz 20 °C W	$I_{AC,R}$ 120 Hz 85 °C mA	Ordering code (composition see below)
$V_R = 450 \text{ V DC}$				
2.2	8 ´ 11.5	97	28	B43821F5225M***
3.3	10 ´ 12.5	65	40	B43821F5335M***
4.7	10 ´ 12.5	45	50	B43821K5475M***
10	10 ´ 20	26	80	B43821F5106M***
22	12.5 ´ 25	14	140	B43821F5226M***
33	16 ´ 25	7.6	180	B43821F5336M***
47	16 ´ 31.5	4.8	220	B43821F5476M***
68	18 ´ 35	2.7	275	B43821A5686M***
100	20 ´ 40	1.8	295	B43821A5107M***

Composition of ordering code

*** = Version

000 = for standard leads, bulk

001 = for kinked leads, bulk (from d ´ l = 10 ´ 20 mm to 18 ´ 40 mm)

002 = for cut leads, bulk (from d ´ l = 10 ´ 12.5 mm to 22 ´ 40 mm)

003 = for crimped leads, blister (from d ´ l = 16 ´ 20 mm to 20 ´ 40 mm)

004 = for J leads, blister (from d ´ l = 10 ´ 12.5 mm to 18 ´ 35 mm)

006 = for taped leads, Ammo pack, lead spacing F = 3.5 mm (for d = 8 mm)

007 = for taped leads, Ammo pack, lead spacing F = 2.5 mm (from d = 5 mm to 6.3 mm)

008 = for taped leads, Ammo pack, lead spacing F = 5.0 mm (from d ´ l = 5 ´ 11 mm to 12.5 ´ 25 mm)

009 = for taped leads, Ammo pack, lead spacing F = 7.5 mm (for d ´ l = 16 ´ 20 ... 16 ´ 31.5 mm and 18 ´ 25 ... 18 ´ 31.5 mm)


012 = for bent 90° leads, blister (for \varnothing 16 and 18 mm)




Useful life

depending on ambient temperature T_A under ripple current operating conditions¹⁾


$V_R = 6.3 \dots 100 \text{ V DC}$



$V_R = 160 \dots 450 \text{ V DC}$




¹⁾ Refer to chapter "General technical information, 5.3 Calculation of useful life" for an explanation on how to interpret the useful life graphs.




B41821, B43821

Standard series 85 °C

Frequency factor of permissible ripple
current I_{AC} versus frequency f
 $V_R \leq 100$ V DC



Frequency factor of permissible ripple
current I_{AC} versus frequency f
 $V_R \leq 160$ V DC





Taping, packing and lead configurations

Taping

Single-ended capacitors are available taped in Ammo pack from diameter 4 to 18 mm as follows:

Lead spacing $F = 2.0 \text{ mm}$ ($\Delta d = 4 \dots 5 \text{ mm}$)

Lead spacing $F = 2.5 \text{ mm}$ ($\Delta d = 4 \dots 6.3 \text{ mm}$)


Lead spacing $F = 3.5 \text{ mm}$ ($\Delta d = 8 \text{ mm}$)

Lead spacing $F = 5.0 \text{ mm}$ ($\Delta d = 4 \dots 12.5 \text{ mm}$)

Lead spacing $F = 7.5 \text{ mm}$ ($\Delta d = 16 \dots 18 \text{ mm}$).

Lead spacing 2.0 mm ($\Delta d = 4 \dots 5 \text{ mm}$)

Last 3 digits of ordering code: 016



Dimensions in mm

Δd	F	H	W	W_0	W_1	W_2	P	P_0	P_1	l_1	t	Dh	D_0
4 ... 5	2.0	18.5	18.0	7.0	9.0	3.0	12.7	12.7	5.10	1.0	0.7	1	4.0
	+0.8 0.2	±0.75	±0.5	min.	±0.5	max.	±1.0	±0.3	±0.7	max.	±0.2	±1.0	±0.2




B41821, B43821

Standard series 85 °C

Lead spacing 2.5 mm ($\Delta d = 4 \dots 6.3$ mm)

Last 3 digits of ordering code: 007




Dimensions in mm

Δd	F	H	W	W_0	W_1	W_2	H_0	P	P_0	P_1	I_1	t	Dh	D_0
4 ... 6.3	2.5	18.5	18.0	5.5	9.0	1.5	16.0	12.7	12.7	5.1	1.0	0.7	1.0	4.0
Tolerance	+0.8 0.2	± 0.75	± 0.5	min.	± 0.5	max.	± 0.5	± 1.0	± 0.2	± 0.5	max.	± 0.2	max.	± 0.2

Lead spacing 3.5 mm ($\Delta d = 8$ mm)

Last 3 digits of ordering code: 006



Dimensions in mm


Δd	F	H	W	W_0	W_1	W_2	P	P_0	P_1	I_1	t	Dh	D_0
8	3.5	18.5	18.0	10	9.0	3.0	12.7	12.7	4.6	1.0	0.7	1.0	4.0
Tolerance	+0.8 0.2	± 1.0	± 0.5	min.	± 0.5	max.	± 1.0	± 0.3	± 0.6	max.	± 0.2	max.	± 0.2

Leads can also run straight through the taping area. Taping is available up to dimensions $d \cdot l = 8 \cdot 15$ mm.




Lead spacing 5.0 mm ($\Delta d = 4 \dots 8$ mm)

Last 3 digits of ordering code: 008



Lead spacing 5.0 mm ($\Delta d = 10 \dots 12.5$ mm)

Last 3 digits of ordering code: 008



Dimensions in mm

Δd	F	H	W	W_0	W_1	W_2	H_0	P	P_0	P_1	l_1	t	Dh	D_0
4 ... 6.3	5.0	18.5	18.0	5.5	9.0	1.5	16.0	12.7	12.7	3.85	1.0	0.6	1.0	4.0
8	5.0	20.0	18.0	10.0	9.0	1.5	16.0	12.7	12.7	3.85	1.0	0.6	1.0	4.0
10		19.0		12.5				12.7	12.7	3.85				
12.5		19.0		12.5				15.0	15.0	5.0				
Tolerance	+0.8 0.2	± 0.75	± 0.5	min.	± 0.5	max.	± 0.5	± 1.0	± 0.2	± 0.5	max.	+0.3 0.2	max.	± 0.2

Taping is available up to dimensions $d \times l = 12.5 \times 25$ mm.

Taping is not available for $d \times l = 8 \times 20$ mm.




B41821, B43821

Standard series 85 °C

Lead spacing 7.5 mm ($\Delta d = 16 \dots 18$ mm)

Last 3 digits of ordering code: 009



Dimensions in mm

Δd	F	H	W	W_0	W_1	W_2	P	P_0	P_1	I_1	t	DP	Dh	D_0
16	7.5	18.5	18.0	12.5	9.0	1.5	30.0	15.0	3.75	1.0	0.7	0	0	4.0
18														
Tolerance	± 0.8	0.5 $+0.75$	± 0.5	min.	± 0.5	max.	± 1.0	± 0.2	± 0.5	max.	± 0.2	± 1.0	± 1.0	± 0.2

Taping is available up to dimensions $d \times l = 16 \times 31.5$ mm and 18×31.5 mm.




Cut or kinked leads

Single-ended capacitors are available with cut or kinked leads. Other lead configurations also available upon request.

Cut leads (Chapter A)

Available for series B41002, B41022, B41044, B41827, B41828, B43044, B43082, B43086, B43088, B43827, B43828.


Last 3 digits of ordering code: 002



KAL1086-R

Case size d x l (mm)	Dimensions (mm) a ±0.5
4 x 7	1.5
5 x 7	2.0
5 x 11	2.0
6.3 x 7	2.5
6.3 x 11	2.5
8 x 7	3.5
8 x 11.5	3.5
8 x 15	3.5
8 x 20	3.5
10 x 12.5	5.0
10 x 16	5.0
10 x 20	5.0
10 x 25	5.0

Case size d x l (mm)	Dimensions (mm) a ±0.5
12.5 x 16	5.0
12.5 x 20	5.0
12.5 x 25	5.0
12.5 x 31.5	5.0
12.5 x 35.5	5.0
12.5 x 40	5.0
16 x 20	7.5
16 x 25	7.5
16 x 31.5	7.5
16 x 35.5	7.5
16 x 40	7.5
18 x 20	7.5
18 x 25	7.5
18 x 31.5	7.5
18 x 35.5	7.5
18 x 40	7.5



B41821, B43821


Standard series 85 °C

Cut leads (Chapter B)


Available for series B41858, B41859, B41863, B41866, B41868, B41888, B41890, B41896, B42824, B42851, B43866, B43867, B43890, B43896.

Last 3 digits of ordering code: 002

With stand-off rubber seal



With flat rubber seal




Case size d ´ l (mm)	Dimensions (mm) a ±0.5
10 ´ 12.5	5.0
10 ´ 16	5.0
10 ´ 20	5.0
12.5 ´ 20	5.0
12.5 ´ 25	5.0
16 ´ 20	7.5
16 ´ 25	7.5
16 ´ 31.5	7.5
16 ´ 35.5	7.5
18 ´ 20	7.5
18 ´ 25	7.5
18 ´ 31.5	7.5
18 ´ 35	7.5
18 ´ 40	7.5




Kinked leads (Chapter A)

Available for series B41002, B41022, B41044, B41827, B41828, B43044, B43082, B43086, B43088, B43827, B43828.

Last 3 digits of ordering code: 001



KAL1137-5



KAL1084-A

Case size d x l (mm)	Dimensions (mm) a ±0.5
4 x 7	1.5
5 x 7	2.0
5 x 11	2.0
6.3 x 7	2.5
6.3 x 11	2.5
8 x 7	3.5
8 x 11.5	3.5
8 x 15	3.5
8 x 20	3.5
10 x 12.5	5.0
10 x 16	5.0
10 x 20	5.0
10 x 25	5.0

Case size d x l (mm)	Dimensions (mm) a ±0.5
12.5 x 16	5.0
12.5 x 20	5.0
12.5 x 25	5.0
12.5 x 31.5	5.0
12.5 x 35.5	5.0
12.5 x 40	5.0
16 x 20	7.5
16 x 25	7.5
16 x 31.5	7.5
16 x 35.5	7.5
16 x 40	7.5
18 x 20	7.5
18 x 25	7.5
18 x 31.5	7.5
18 x 35.5	7.5
18 x 40	7.5



B41821, B43821


Standard series 85 °C

Kinked leads (Chapter B)


Available for series B41858, B41859, B41863, B41866, B41868, B41888, B41890, B41896, B42824, B42851, B43866, B43867, B43890, B43896.

Last 3 digits of ordering code: 001

With stand-off rubber seal




KAL1081-K




KAL1083-2

With flat rubber seal



KAL1082-T



KAL1084-A

Case size d ´ l (mm)	Dimensions (mm) a ±0.5
10 ´ 20	5.0
12.5 ´ 20	5.0
12.5 ´ 25	5.0
16 ´ 20	7.5
16 ´ 25	7.5
16 ´ 31.5	7.5
16 ´ 35.5	7.5
18 ´ 20	7.5
18 ´ 25	7.5
18 ´ 31.5	7.5
18 ´ 35	7.5
18 ´ 40	7.5



PAPR leads (Protection Against Polarity Reversal)

These lead configurations ensure correct placement of the capacitor on the PCB with regard to polarity. PAPR leads are available for diameters from 10 mm up to 18 mm.


There are three configurations available: Crimped leads, J leads, bent 90° leads

Available for series B41858, B41859, B41863, B41866, B41868, B41888, B41890, B41896, B42824, B42851, B43866, B43867, B43890, B43896.


Crimped leads

Last 3 digits of ordering code: 003



With stand-off rubber seal



With flat rubber seal



Suggestion for PCB hole diameter



Case size d ´ l (mm)	Dimensions (mm)					
	B ±0.2	C ±0.5	D ±0.1	E ±0.1	a ±0.5	∅b
16 ´ 20	1.5	3.0	1.3	0.3	7.5	0.8 ±0.05
16 ´ 25	1.5	3.0	1.3	0.3	7.5	0.8 ±0.05
16 ´ 31.5	1.5	3.0	1.3	0.3	7.5	0.8 ±0.05
16 ´ 35.5	1.5	3.0	1.3	0.3	7.5	0.8 ±0.05
18 ´ 20	1.5	3.0	1.3	0.3	7.5	0.8 ±0.1
18 ´ 25	1.5	3.0	1.3	0.3	7.5	0.8 ±0.1
18 ´ 31.5	1.5	3.0	1.3	0.3	7.5	0.8 ±0.1
18 ´ 35	1.5	3.0	1.3	0.3	7.5	0.8 ±0.1
18 ´ 40	1.5	3.0	1.3	0.3	7.5	0.8 ±0.1




B41821, B43821

Standard series 85 °C


J leads

Last 3 digits of ordering code: 004




Suggestion for PCB hole diameter

Suggestion for PCB hole diameter,
wire $\varnothing 0.6$ mm



Suggestion for PCB hole diameter,
wire $\varnothing 0.8$ mm




Case size d ´ l (mm)	Dimensions (mm)				
	C ±0.5	E ±0.5	J ±0.2	a ±0.5	Ab
10 ´ 12.5	3.2	0.7	1.2	5.0	0.6 ±0.05
10 ´ 16	3.2	0.7	1.2	5.0	0.6 ±0.05
10 ´ 20	3.2	0.7	1.2	5.0	0.6 ±0.05
12.5 ´ 20	3.2	0.7	1.2	5.0	0.6 ±0.05
12.5 ´ 25	3.2	0.7	1.2	5.0	0.6 ±0.05
16 ´ 20	3.5	0.7	1.6	7.5	0.8 ±0.05
16 ´ 25	3.5	0.7	1.6	7.5	0.8 ±0.05
16 ´ 31.5	3.5	0.7	1.6	7.5	0.8 ±0.05
16 ´ 35.5	3.5	0.7	1.6	7.5	0.8 ±0.05
18 ´ 20	3.5	0.7	1.6	7.5	0.8 ±0.1
18 ´ 25	3.5	0.7	1.6	7.5	0.8 ±0.1
18 ´ 31.5	3.5	0.7	1.6	7.5	0.8 ±0.1
18 ´ 35	3.5	0.7	1.6	7.5	0.8 ±0.1



Bent 90 ° leads for horizontal mounting pinning

Last 3 digits of ordering code: 012



Case size d × l (mm)	Dimensions (mm)				
	C ±0.5	E ±0.5	F ±0.5	a ±0.5	±b
16 × 20	4.0	4.0	12.0	7.5	0.8 ±0.05
16 × 25	4.0	4.0	12.0	7.5	0.8 ±0.05
16 × 31.5	4.0	4.0	12.0	7.5	0.8 ±0.05
16 × 35.5	4.0	4.0	12.0	7.5	0.8 ±0.05
18 × 20	4.0	4.0	13.0	7.5	0.8 ±0.1
18 × 25	4.0	4.0	13.0	7.5	0.8 ±0.1
18 × 31.5	4.0	4.0	13.0	7.5	0.8 ±0.1
18 × 35	4.0	4.0	13.0	7.5	0.8 ±0.1
18 × 40	4.0	4.0	13.0	7.5	0.8 ±0.1

Bent leads for diameter 12.5 mm available upon request.




B41821, B43821

Standard series 85 °C

Packing units and box dimensions

Ammo pack

Valid for series B41002, B41022, B41044, B41827, B41828, B43044, B43082, B43086, B43088, B43827, B43828.




Case size d × l mm	Dimensions (mm)			Packing units pcs.
	A _{max}	B _{max}	C _{max}	
4 × 7	330	50	196	2000
5 × 7	330	50	226	2000
5 × 11	330	50	226	2000
6.3 × 7	330	50	286	2000
6.3 × 11	330	50	286	2000
8 × 7	330	50	246	1000
8 × 11.5	330	50	246	1000
8 × 15	330	50	246	500
10 × 12.5	330	50	196	500
10 × 16	330	54	196	500
10 × 20	330	58	196	500
12.5 × 20	341	60	272	500
12.5 × 25	341	65	272	500
16 × 25	320	65	270	300
16 × 31.5	315	65	275	300
18 × 20	315	65	275	250
18 × 25	315	65	275	250
18 × 31.5	315	65	275	250



Ammo pack

Valid for series B41858, B41859, B41863, B41866, B41868, B41888, B41890, B41896, B42824, B42851, B43866, B43867, B43890, B43896.



Case size d × l mm	Dimensions (mm)			Packing units pcs.
	A _{max}	B _{max}	C _{max}	
8 × 11.5	345	55	240	1000
10 × 12.5	345	55	280	750
10 × 16	345	60	200	500
10 × 20	345	60	200	500
12.5 × 20	345	65	280	500
12.5 × 25	345	65	280	500
16 × 20	315	65	275	300
16 × 25	315	65	275	300
16 × 31.5	315	65	275	300
18 × 20	315	65	275	250
18 × 25	315	65	275	250
18 × 31.5	315	65	275	250



B41821, B43821

Standard series 85 °C

Overview of packing units and code numbers for case sizes 4 x 7 ... 16 x 40

Valid for series B41002, B41022, B41044, B41827, B41828, B43044, B43082, B43086, B43088, B43827, B43828.

Case size d x l mm	Standard, bulk pcs.	Taped, Ammo pack pcs.			Kinked leads, bulk pcs.	Cut leads, bulk pcs.
4 x 7	10000	2000			15000	15000
5 x 7	7500	2000			10000	10000
5 x 11	5000	2000			10000	10000
6.3 x 7	5000	2000			10000	10000
6.3 x 11	5000	2000			5000	5000
8 x 7	5000	1000			5000	5000
8 x 11.5	2500	1000			4000	4000
8 x 15	2000	1000			2500	2500
8 x 20	1500				2000	2000
10 x 12.5	2000	500			2500	2500
10 x 16	1500	500			2000	2000
10 x 20	1000	500			1500	1500
10 x 25	1000	500			1250	1250
12.5 x 16	750	500			1000	1000
12.5 x 20	750	500			500	500
12.5 x 25	750	500			500	500
12.5 x 31.5	500				750	750
12.5 x 35.5	500				750	750
12.5 x 40	500				750	750
16 x 20	375	300			500	500
16 x 25	375	300			500	500
16 x 31.5	250	300			375	375
16 x 35.5	250				375	375
16 x 40	250				375	375
The last three digits of the complete ordering code state the lead configuration	000	Code	F (mm)	d (mm)	001	002
		006	3.5	8		
		007	2.5	4 ... 6.3		
		008	5.0	4 ... 12.5		
		009	7.5	16 ... 18		
		016	2.0	4 ... 5		



Overview of packing units and code numbers for case sizes 18 x 20 ... 18 x 40

Valid for series B41002, B41022, B41044, B41827, B41828, B43044, B43082, B43086, B43088, B43827, B43828.

Case size d x l mm	Standard, bulk pcs.	Taped, Ammo pack pcs.			Kinked leads, bulk pcs.	Cut leads, bulk pcs.
18 x 20	250	250			100	100
18 x 25	250	250			100	100
18 x 31.5	250	250			100	100
18 x 35.5	250				100	100
18 x 40	250				100	100
The last three digits of the complete ordering code state the lead configuration	000	Code	F (mm)	d (mm)	001	002
		009	7.5	16 ... 18		



B41821, B43821

Standard series 85 °C

Overview of packing units and code numbers for case sizes 8 ´ 11.5 ... 16 ´ 35.5

Valid for series B41858, B41859, B41863, B41866, B41868, B41888, B41890, B41896, B42824, B42851, B43866, B43867, B43890, B43896.

						PAPR			
Case size d ´ l mm	Stan- dard, bulk pcs.	Taped, Ammo pack pcs.			Kinked leads, bulk pcs.	Cut leads, bulk pcs.	Crimped leads, blister pcs.	J leads, blister pcs.	Bent 90° leads, blister pcs.
8 ´ 11.5	1000	1000							
10 ´ 12.5	1000	750				1000		675	
10 ´ 16	1000	500				1000		675	
10 ´ 20	500	500			500	500		500	
12.5 ´ 20	350	500			350	350		300	1)
12.5 ´ 25	250	500			500	500		225	1)
12.5 ´ 30	200								
12.5 ´ 35	175								
12.5 ´ 40	175								
16 ´ 20	250	300			200	200	200	200	120
16 ´ 25	250	300			200	200	200	200	120
16 ´ 31.5	200	300			250	250	344	344	120
16 ´ 35.5	100				100	100	150	150	150
The last three digits of the complete ordering code state the lead configuration	000	Code	F (mm)	d (mm)	001	002	003	004	012
		006	3.5	8					
		008	5	5...12.5					
		009	7.5	16...18					

1) Available upon request



Overview of packing units and code numbers for case sizes 18 ´ 20 ... 18 ´ 40

Valid for series B41858, B41859, B41863, B41866, B41868, B41888, B41890, B41896, B42824, B42851, B43866, B43867, B43890, B43896.

						PAPR			
Case size d ´ l mm	Stand- ard, bulk pcs.	Taped, Ammo pack pcs.			Kinked leads, bulk pcs.	Cut leads, bulk pcs.	Crimped leads, blister pcs.	J leads, blister pcs.	Bent 90° leads, blister pcs.
18 ´ 20	175	250			175	175	200	200	120
18 ´ 25	150	250			150	150	200	200	120
18 ´ 31.5	100	250			100	100	150	150	120
18 ´ 35	100				100	100	150	150	150
18 ´ 40	125				100	100	120		72
The last three digits of the complete ordering code state the lead configuration	000	Code	F (mm)	d (mm)	001	002	003	004	012
		009	7.5	16...18					



Cautions and warnings

Personal safety

The electrolytes used by EPCOS have not only been optimized with a view to the intended application, but also with regard to health and environmental compatibility. They do not contain any solvents that are detrimental to health, e.g. dimethyl formamide (DMF) or dimethyl acetamide (DMAC).

Furthermore, part of the high-voltage electrolytes used by EPCOS are self-extinguishing. They contain flame-retarding substances which will quickly extinguish any flame that may have been ignited.

As far as possible, EPCOS does not use any dangerous chemicals or compounds to produce operating electrolytes. However, in exceptional cases, such materials must be used in order to achieve specific physical and electrical properties because no safe substitute materials are currently known. However, the amount of dangerous materials used in our products has been limited to an absolute minimum. Nevertheless, the following rules should be observed when handling aluminum electrolytic capacitors:

- Any escaping electrolyte should not come into contact with eyes or skin.
- If electrolyte does come into contact with the skin, wash the affected parts immediately with running water. If the eyes are affected, rinse them for 10 minutes with plenty of water. If symptoms persist, seek medical treatment.
- Avoid breathing in electrolyte vapor or mists. Workplaces and other affected areas should be well ventilated. Clothing that has been contaminated by electrolyte must be changed and rinsed in water.



Product safety

The table below summarizes the safety instructions that must be observed without fail. A detailed description can be found in the relevant sections of chapter "General technical information".

Topic	Safety information	Reference chapter "General technical information"
Polarity	Make sure that polar capacitors are connected with the right polarity.	1 "Basic construction of aluminum electrolytic capacitors"
Reverse voltage	Voltages polarity classes should be prevented by connecting a diode.	3.1.6 "Reverse voltage"
Upper category temperature	Do not exceed the upper category temperature.	7.2 "Maximum permissible operating temperature"
Maintenance	Make periodic inspections of the capacitors. Before the inspection, make sure that the power supply is turned off and carefully discharge the electricity of the capacitors. Do not apply any mechanical stress to the capacitor terminals.	10 "Maintenance"
Mounting position of screw-terminal capacitors	Do not mount the capacitor with the terminals (safety vent) upside down.	11.1. "Mounting positions of capacitors with screw terminals"
Mounting of single-ended capacitors	The internal structure of single-ended capacitors might be damaged if excessive force is applied to the lead wires. Avoid any compressive, tensile or flexural stress. Do not move the capacitor after soldering to PC board. Do not pick up the PC board by the soldered capacitor. Do not insert the capacitor on the PC board with a hole space different to the lead space specified.	11.4 "Mounting considerations for single-ended capacitors"
Robustness of terminals	The following maximum tightening torques must not be exceeded when connecting screw terminals: M5: 2 Nm M6: 2.5 Nm	11.3 "Mounting torques"
Soldering	Do not exceed the specified time or temperature limits during soldering.	11.5 "Soldering"



Topic	Safety information	Reference chapter "General technical information"
Soldering, cleaning agents	Do not allow halogenated hydrocarbons to come into contact with aluminum electrolytic capacitors.	11.6 "Cleaning agents"
Passive flammability	Avoid external energy, such as fire or electricity.	8.1 "Passive flammability"
Active flammability	Avoid overload of the capacitors.	8.2 "Active flammability"
		Reference chapter "Capacitors with screw terminals"
Breakdown strength of insulating sleeves	Do not damage the insulating sleeve, especially when ring clips are used for mounting.	"Screw terminals accessories"



Symbols and terms

Symbol	English	German
C	Capacitance	Kapazität
C_R	Rated capacitance	Nennkapazität
C_S	Series capacitance	Serienkapazität
$C_{S,T}$	Series capacitance at temperature T	Serienkapazität bei Temperatur T
C_f	Capacitance at frequency f	Kapazität bei Frequenz f
d	Case diameter, nominal dimension	Gehäusedurchmesser, Nennmaß
d_{max}	Maximum case diameter	Maximaler Gehäusedurchmesser
ESL	Self-inductance	Eigeninduktivität
ESR	Equivalent series resistance	Ersatzserienwiderstand
ESR_f	Equivalent series resistance at frequency f	Ersatzserienwiderstand bei Frequenz f
ESR_T	Equivalent series resistance at temperature T	Ersatzserienwiderstand bei Temperatur T
f	Frequency	Frequenz
I	Current	Strom
I_{AC}	Alternating current (ripple current)	Wechselstrom
$I_{AC,rms}$	Root-mean-square value of alternating current	Wechselstrom, Effektivwert
$I_{AC,f}$	Ripple current at frequency f	Wechselstrom bei Frequenz f
$I_{AC,max}$	Maximum permissible ripple current	Maximal zulässiger Wechselstrom
$I_{AC,R}$	Rated ripple current	Nennwechselstrom
$I_{AC,R} (B)$	Rated ripple current for base cooling	Nennwechselstromstrom für Bodenkühlung
I_{leak}	Leakage current	Reststrom
$I_{leak,op}$	Operating leakage current	Betriebsreststrom
l	Case length, nominal dimension	Gehäuselänge, Nennmaß
l_{max}	Maximum case length (without terminals and mounting stud)	Maximale Gehäuselänge (ohne Anschlüsse und Gewindebolzen)
R	Resistance	Widerstand
R_{ins}	Insulation resistance	Isolationswiderstand
R_{symm}	Balancing resistance	Symmetrierwiderstand
T	Temperature	Temperatur
ΔT	Temperature difference	Temperaturdifferenz
T_A	Ambient temperature	Umgebungstemperatur
T_C	Case temperature	Gehäusetemperatur
T_B	Capacitor base temperature	Temperatur des Becherbodens
t	Time	Zeit
Δt	Period	Zeitraum
t_b	Service life (operating hours)	Brauchbarkeitsdauer (Betriebszeit)



B41821, B43821

Standard series 85 °C

Symbol	English	German
V	Voltage	Spannung
V_F	Forming voltage	Formierspannung
V_{op}	Operating voltage	Betriebsspannung
V_R	Rated voltage, DC voltage	Nennspannung, Gleichspannung
V_S	Surge voltage	Spitzenspannung
X_C	Capacitive reactance	Kapazitiver Blindwiderstand
X_L	Inductive reactance	Induktiver Blindwiderstand
Z	Impedance	Scheinwiderstand
Z_T	Impedance at temperature T	Scheinwiderstand bei Temperatur T
$\tan \delta$	Dissipation factor	Verlustfaktor
I	Failure rate	Ausfallrate
ϵ_0	Absolute permittivity	Elektrische Feldkonstante
ϵ_r	Relative permittivity	Dielektrizitätszahl
w	Angular velocity; 2 p f	Kreisfrequenz; 2 p f

Note

All dimensions are given in mm.

The following applies to all products named in this publication:

1. Some parts of this publication contain statements about the suitability of our products for certain areas of application. These statements are based on our knowledge of typical requirements that are often placed on our products in the areas of application concerned. We nevertheless expressly point out that such statements cannot be regarded as binding statements about the suitability of our products for a particular customer application. As a rule, EPCOS is either unfamiliar with individual customer applications or less familiar with them than the customers themselves. For these reasons, it is always ultimately incumbent on the customer to check and decide whether an EPCOS product with the properties described in the product specification is suitable for use in a particular customer application.
2. We also point out that in individual cases, a malfunction of electronic components or failure before the end of their usual service life cannot be completely ruled out in the current state of the art, even if they are operated as specified. In customer applications requiring a very high level of operational safety and especially in customer applications in which the malfunction or failure of an electronic component could endanger human life or health (e.g. in accident prevention or lifesaving systems), it must therefore be ensured by means of suitable design of the customer application or other action taken by the customer (e.g. installation of protective circuitry or redundancy) that no injury or damage is sustained by third parties in the event of malfunction or failure of an electronic component.
3. The warnings, cautions and product-specific notes must be observed.
4. In order to satisfy certain technical requirements, some of the products described in this publication may contain substances subject to restrictions in certain jurisdictions (e.g. because they are classed as hazardous). Useful information on this will be found in our Material Data Sheets on the Internet (www.epcos.com/material). Should you have any more detailed questions, please contact our sales offices.
5. We constantly strive to improve our products. Consequently, the products described in this publication may change from time to time. The same is true of the corresponding product specifications. Please check therefore to what extent product descriptions and specifications contained in this publication are still applicable before or when you place an order. We also reserve the right to discontinue production and delivery of products. Consequently, we cannot guarantee that all products named in this publication will always be available. The aforementioned does not apply in the case of individual agreements deviating from the foregoing for customer-specific products.
6. Unless otherwise agreed in individual contracts, all orders are subject to the current version of the "General Terms of Delivery for Products and Services in the Electrical Industry" published by the German Electrical and Electronics Industry Association (ZVEI).
7. The trade names EPCOS, BAOKE, Alu-X, CeraDiode, CSMP, CSSP, CTVS, DeltaCap, DigiSiMic, DSSP, FormFit, MiniBlue, MiniCell, MKK, MKD, MLSC, MotorCap, PCC, PhaseCap, PhaseCube, PhaseMod, PhiCap, SIFERRIT, SIFI, SIKOREL, SilverCap, SIMDAD, SiMic, SIMID, SineFormer, SIOV, SIP5D, SIP5K, ThermoFuse, WindCap are trademarks registered or pending in Europe and in other countries. Further information will be found on the Internet at www.epcos.com/trademarks.